



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	CA6-11K-F
Product ID:	GJL1201318R0001
EAN:	4013614050985
Catalog Description:	CA6-11K-F Auxiliary Contact
Long Description:	CA6-11K-F is an auxiliary contact for side with 2 auxiliary contact and flat pin connection.

Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Mini Contactors Accessories

Ordering

EAN:	4013614050985
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85389099

Container Information

Package Level 1 Width:	112 mm
Package Level 1 Length:	142 mm
Package Level 1 Height:	62 mm
Package Level 1 Gross Weight:	0.315 kg
Package Level 1 EAN:	4013614412134
Package Level 1 Units:	10 piece

Dimensions

Product Net Width:	20.3 mm
Product Net Height:	48.5 mm
Product Net Depth:	46.5 mm
Product Net Weight:	0.025 kg

Technical

Rated Operational Voltage:	Auxiliary Circuit 12 ... 240 V DC Auxiliary Circuit 12 ... 500 V AC/DC
Rated Frequency (f):	Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC
Rated Impulse Withstand Voltage (U _{imp}):	Auxiliary Circuit 6 kV
Rated Insulation Voltage (U _i):	690 V
Degree of Protection:	IP20
Standards:	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1
Number of Auxiliary Contacts NO:	1
Number of Main Contacts NC:	0
Number of Main Contacts NO:	0
Conventional Free-air Thermal Current (I _{th}):	Auxiliary Circuit 6 A
Product Name:	Auxiliary Contact
Suitable For:	K6-F KC6-F
Suitable for Product Class:	Mini Contactors

Environmental

Ambient Air Temperature:	Operation -25 ... +55 °C Storage -40 ... +80 °C
Maximum Operating Altitude Permissible:	2000 m
Resistance to Shock acc. to IEC 60068-2-27:	11 ms Pulse 15g
Resistance to Vibrations acc. to IEC 60068-2-6:	5g / 5 ... 150 Hz
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Auxiliary Circuit 600 V AC/DC
Contact Rating UL/CSA:	A600

Certificates and Declarations (Document Number)

CB Certificate:	1SAA938001-2001
CCC Certificate:	1SAA938000-3803
cUL Certificate:	cUL_E48139
cUR Certificate:	1SAA938000-1901
Declaration of Conformity - CE:	1SAD938510-0001
EAC Certificate:	1SAA938002-2701
GL Certificate:	1SAA938000-0403
RMRS Certificate:	1SAA938001-0703
RoHS Information:	1SAA938004-4401
UL Certificate:	UL_E48139
UR Certificate:	1SAA938000-1801

Classifications

Object Classification Code:	K
eClass:	7.0 27371302
UNSPSC:	39121500





Automatización Eléctrica
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

Product	Code	Reference	Product link
CA6-11K-F Auxiliary Contact	GJL1201318R0001	CA6-11KF	Buy on EAN