



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	CAF6-02N
Product ID:	GJL1201330R0012
EAN:	4013614148415
Catalog Description:	CAF6-02N Auxiliary Contact
Long Description:	The CAF6-02N is an auxiliary contact for front mounting with 2 auxiliary contact and screw terminals.

Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Mini Contactors Accessories
 Parts & Services » Low Voltage Products and Systems » Control Products » Arc Guard Systems » Service » Spares and Consumables

Ordering

EAN:	4013614148415
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85389099

Container Information

Package Level 1 Width:	115 mm
Package Level 1 Length:	280 mm
Package Level 1 Height:	54 mm
Package Level 1 Gross Weight:	0.24 kg
Package Level 1 EAN:	4013614412332
Package Level 1 Units:	10 piece

Dimensions

Product Net Width:	47.5 mm
Product Net Height:	29 mm
Product Net Depth:	26.5 mm
Product Net Weight:	0.02 kg

Technical

Rated Operational Voltage:	Auxiliary Circuit 12 ... 240 V DC Auxiliary Circuit 12 ... 500 V AC/DC
Rated Frequency (f):	Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC
Rated Impulse Withstand Voltage (U _{imp}):	Auxiliary Circuit 6 kV
Rated Insulation Voltage (U _i):	690 V
Degree of Protection:	IP20
Connecting Capacity-Auxiliary Circuit:	Flexible with Ferrule 1/2x 1 ... 2.5 mm ² Flexible 1/2x 1 ... 2.5 mm ² Rigid 1/2x 1 ... 4 mm ²
Tightening Torque:	Auxiliary Circuit 0.8 ... 1.1 N·m
Wire Stripping Length:	Auxiliary Circuit 9 mm
Standards:	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1
Number of Auxiliary Contacts NO:	0
Number of Main Contacts NC:	0
Number of Main Contacts NO:	0
Conventional Free-air Thermal Current (I _{th}):	Auxiliary Circuit 6 A
Product Name:	Auxiliary Contact
Suitable For:	B6-30-01 BC6-30-01 B7-30-01 BC7-30-01 VB6-30-01 VBC6-30-01

VB7-30-01
VBC7-30-01
VB6A-30-01
VBC6A-30-01
VB7A-30-01
VBC7A-30-01

Suitable for Product Class: Mini Contactors

Environmental

Ambient Air Temperature: Operation -25 ... +55 °C
Storage -40 ... +80 °C

Maximum Operating Altitude Permissible: 2000 m

Resistance to Shock acc. to IEC 60068-2-27: 11 ms Pulse 15g

Resistance to Vibrations acc. to IEC 60068-2-6: 5g / 5 ... 150 Hz

RoHS Status: Following EU Directive 2002/95/EC August 18, 2005 and amendment

Technical UL/CSA

Maximum Operating Voltage UL/CSA: Auxiliary Circuit 600 V AC/DC

Connecting Capacity Auxiliary Circuit UL/CSA: Stranded 1/2x 22 ... 10 AWG

Tightening Torque UL/CSA: Auxiliary Circuit 7 in·lb

Contact Rating UL/CSA: A600

Certificates and Declarations (Document Number)

CCC Certificate: 1SAA938000-3803

cUL Certificate: cUL_E48139

Declaration of Conformity - CE: 1SAD938510-0001

EAC Certificate: 1SAA938002-2701

GL Certificate: 1SAA938000-0403

RMRS Certificate: 1SAA938001-0703

RoHS Information: 1SAA938004-4401

UL Certificate: UL_E48139

Classifications

Object Classification Code: K

eClass: 7.0 27371302

UNSPSC: 39121500





Automatización Eléctrica
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

Product	Code	Reference	Product link
CAF6-02N Auxiliary Contact	GJL1201330R0012	CAF6-02N	Buy on EAN