



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. <u>HERE</u>

#### AT3 10-24/35-4



#### Advantages

Low weight and small size (compared to isolating transformers)

Very high efficiency

Inverse operation possible

Patented assembly technology to lower heat losses

Very good corrosion protection and low noise thanks to BLOCKIMPEX vacuum impregnation

Fixed, contact protected screw connection terminals complying with UVV BGV  ${\sf A3}$ 

Multifunctional fixing rails with 12 oval slots


Enlarged fixing rail for easy installation from above

Integrated crane eyes

### **Applications**

Autotransformer for adjustment of the voltage on the input and output sides with no requirement for electrical isolation.

#### Sample application



#### Standards



Autotransformer to: VDE 0570 Teil 2-13, DIN EN 61558-2-13, EN 61558-2-13, IEC 61558-2-13, UL 5085-1/-2, CSA 22.2 No.66

## Approvals



UL 5085-1/-2, CSA 22.2 No.66





# Autotransformer AT3 10-24/35-4

	Туре	AT3 10-24/35-4		Туре	AT3 10-24/35-4
Ĵ٢	Input		30	Terminal and mounting	
1+	Rated input voltage	3 x 240/346 Vac	<u>س</u> _	Fixing method	Fixing rail
	Rated frequency	50 - 60 Hz		Fixing screws	M8
ta	Output		ta	Terminals	Screw-type terminals
data	Rated output voltage	3 x 400 Vac	data	Measures and weights	
В	Rated Power	10000 VA	<u></u>	Weight	39.30 kg
.은	Vector group	YNaO	.e	Core type	3 UI 150/65
Electrical	Efficiency	95 %	la la		
吕	Approvals		Mechanical		<b>D</b> ~
	Approvals	cURus	Š		
	Environment				
	Ambient temperature max.	40 °C			
	Safety and protection				280.0
	Туре	Open type			
	Class of Insulation System	F			0-
	Protection index	IP 00		350.0 → 162.	
	Safety class (prepared)	1			
	Short circuit strength	non-short-circuit proof			
	Test voltage	4000 Vac, 50 Hz			
	Order numbers				
	Order Number	AT3 10-24/35-4			





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
Autotransformer PRI 3 x 200/208 - 3 x 690 Vac, SEC 2000 - 250000 VA, 3 x 400 Vac	AT31024354	AT3 10-24/35-4	Buy on EAN