



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. <u>HERE</u>

AT3 110-24/35-4



Advantages

Low weight and small size (compared to isolating transformers)

Very high efficiency

Inverse operation possible

Patented assembly technology to lower heat losses

Very good corrosion protection and low noise thanks to BLOCKIMPEX vacuum impregnation

Fixed, contact protected screw connection terminals complying with UVV BGV ${\sf A3}$

Multifunctional fixing rails with 12 oval slots


Enlarged fixing rail for easy installation from above

Integrated crane eyes

Applications

Autotransformer for adjustment of the voltage on the input and output sides with no requirement for electrical isolation.

Sample application



Standards



Autotransformer to: VDE 0570 Teil 2-13, DIN EN 61558-2-13, EN 61558-2-13, IEC 61558-2-13, UL 5085-1/-2, CSA 22.2 No.66

Approvals




UL 5085-1/-2, CSA 22.2 No.66





Autotransformer AT3 110-24/35-4

Туре	AT3 110-24/35-4	Type
F Input		Terminal and mountin
Rated input voltage	3 x 240/346 Vac	Fixing method
Rated frequency	50 - 60 Hz	Fixing screws
Output Rated output voltage Rated Power Vector group Efficiency Approvals		Terminals
Rated output voltage	3 x 400 Vac	Terminals Measures and weight
Rated Power	110000 VA	₹ Weight
Vector group	YNaO	Core type
Efficiency	98 %	ie l
Approvals		Weight Core type
Approvals	cURus	
Environment		
Ambient temperature max.	40 °C	
Safety and protection		
Туре	Open type	000000
Class of Insulation System	F	
Protection index	IP 00	530.0
Safety class (prepared)	1	
Short circuit strength	non-short-circuit proof	
Test voltage	4000 Vac, 50 Hz	
Order numbers		
Order Number	AT3 110-24/35-4	











Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
Autotransformer PRI 3 x 200/208 - 3 x 690 Vac, SEC 2000 - 250000 VA, 3 x 400 Vac	AT311024354	AT3 110-24/35-4	Buy on EAN