



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. <u>HERE</u>

#### AT3 160-69-4



#### Advantages

Low weight and small size (compared to isolating transformers)

Very high efficiency

Inverse operation possible

Patented assembly technology to lower heat losses

Very good corrosion protection and low noise thanks to BLOCKIMPEX vacuum impregnation

Fixed, contact protected screw connection terminals complying with UVV BGV  ${\sf A3}$ 

Multifunctional fixing rails with 12 oval slots


Enlarged fixing rail for easy installation from above

Integrated crane eyes

### **Applications**

Autotransformer for adjustment of the voltage on the input and output sides with no requirement for electrical isolation.

#### Sample application



#### Standards



Autotransformer to: VDE 0570 Teil 2-13, DIN EN 61558-2-13, EN 61558-2-13, IEC 61558-2-13


## Approvals





# Autotransformer AT3 160-69-4

	Type	AT3 160-69-4		Type		AT3 160-69-4
Ĵ٢	Input		0 1	Type Terminal and mounting Fixing method		
1+	Rated input voltage	3 x 690 Vac	۳.	Fixing method		Fixing rail
	Rated frequency	50 - 60 Hz	_	Fixing screws		M12
data	Output		data	Terminals		Screw-type terminals
	Rated output voltage	3 x 400 Vac		Measures and weights		
	Rated Power	160000 VA	B	Weight		334.00 kg
.은	Vector group	YNaO	.9	Core type		3 UI 300/125
Ctl	Efficiency	98 %	٦g			
Electrical	Approvals		Mechanical			(ELEC.)
	Approvals	-	Š		<u>_</u> _	
	Environment				<b>=</b> _'_	
	Ambient temperature max.	40 °C				550.0
	Safety and protection					
	Туре	Open type			-	200.0
	Class of Insulation System	F				190.0
	Protection index	IP 00		600.0	0.0	
	Safety class (prepared)	1				~
	Short circuit strength	non-short-circuit proof				
	Test voltage	4000 Vac, 50 Hz				
	Order numbers					
	Order Number	AT3 160-69-4				









Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
Autotransformer PRI 3 x 200/208 - 3 x 690 Vac, SEC 2000 - 250000 VA, 3 x 400 Vac	AT3160694	AT3 160-69-4	Buy on EAN