




At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. <u>HERE</u>



## Advantages

Low weight and small size (compared to isolating transformers)

Very high efficiency

Inverse operation possible

Patented assembly technology to lower heat losses

Very good corrosion protection and low noise thanks to BLOCKIMPEX vacuum impregnation

Fixed, contact protected screw connection terminals complying with UVV BGV  ${\sf A3}$ 

Multifunctional fixing rails with 12 oval slots


Enlarged fixing rail for easy installation from above

Integrated crane eyes

# **Applications**

Autotransformer for adjustment of the voltage on the input and output sides with no requirement for electrical isolation.

## Sample application



#### Standards



Autotransformer to: VDE 0570 Teil 2-13, DIN EN 61558-2-13, EN 61558-2-13, IEC 61558-2-13, UL 5085-1/-2, CSA 22.2 No.66

# Approvals




UL 5085-1/-2, CSA 22.2 No.66





# Autotransformer AT3 2-38/42-4

	Туре	AT3 2-38/42-4
ſĹ	Input .	
+	Rated input voltage	3 x 380/415 Vac
	Rated frequency	50 - 60 Hz
Electrical data	Output	
쁑 i	Rated output voltage	3 x 400 Vac
ल	Rated Power	2000 VA
.일	Vector group	YNaO
벙니	Efficiency	78 %
음	Approvals	
	Approvals	cURus
	Environment	
	Ambient temperature max.	40 °C
	Safety and protection	
:	Туре	Open type
	Class of Insulation System	F
- 1	Protection index	IP 00
	Safety class (prepared)	I
	Short circuit strength	non-short-circuit proof
	Test voltage	4000 Vac, 50 Hz
	Order numbers	
Ī	Order Number	AT3 2-38/42-4











Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
Autotransformer PRI 3 x 200/208 - 3 x 690 Vac, SEC 2000 - 250000 VA, 3 x 400 Vac	AT3238424	AT3 2-38/42-4	Buy on EAN