



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. <u>HERE</u>



### Advantages

Low weight and small size (compared to isolating transformers)

Very high efficiency

Inverse operation possible

Patented assembly technology to lower heat losses

Very good corrosion protection and low noise thanks to BLOCKIMPEX vacuum impregnation

Fixed, contact protected screw connection terminals complying with UVV BGV  ${\sf A3}$ 

Multifunctional fixing rails with 12 oval slots


Enlarged fixing rail for easy installation from above

Integrated crane eyes

## **Applications**

Autotransformer for adjustment of the voltage on the input and output sides with no requirement for electrical isolation.

### Sample application



#### Standards



Autotransformer to: VDE 0570 Teil 2-13, DIN EN 61558-2-13, EN 61558-2-13, IEC 61558-2-13, UL 5085-1/-2, CSA 22.2 No.66

# **Approvals**




UL 5085-1/-2, CSA 22.2 No.66





# Autotransformer AT3 2-58/60-4

	Туре	AT3 2-58/60-4		Туре	AT3 2
յ <b>+</b>	Input		30	Terminal and mounting	
	Rated input voltage	3 x 575/600 Vac	<u> ۳</u>	Fixing method	Fixing rai
	Rated frequency	50 - 60 Hz		Fixing screws	M6
al data	Output		data	Terminals	Screw-ty
	Rated output voltage	3 x 400 Vac	<del>g</del>	Measures and weights	
	Rated Power	2000 VA	<u></u>	Weight	7.50 kg
.2	Vector group	YNaO	<u>ان</u>	Core type	3 UI 90/3
Electrical	Efficiency	88 %	le le		
음	Approvals		Mechanical		
	Approvals	cURus	Š		_/
	Environment				T
	Ambient temperature max.	40 °C			
	Safety and protection				175.0
	Туре	Open type			
	Class of Insulation System	F			<b>≒</b> ₽ 🔨 🦠
	Protection index	IP 00		220.0	
	Safety class (prepared)	1			
	Short circuit strength	non-short-circuit proof			
	Test voltage	4000 Vac, 50 Hz			
	Order numbers				
	Order Number	AT3 2-58/60-4			











Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
Autotransformer PRI 3 x 200/208 - 3 x 690 Vac, SEC 2000 - 250000 VA, 3 x 400 Vac	AT3258604	AT3 2-58/60-4	Buy on EAN