



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. <u>HERE</u>



Advantages

Low weight and small size (compared to isolating transformers)

Very high efficiency

Inverse operation possible

Patented assembly technology to lower heat losses

Very good corrosion protection and low noise thanks to BLOCKIMPEX vacuum impregnation

Fixed, contact protected screw connection terminals complying with UVV BGV ${\sf A3}$

Multifunctional fixing rails with 12 oval slots


Enlarged fixing rail for easy installation from above

Integrated crane eyes

Applications

Autotransformer for adjustment of the voltage on the input and output sides with no requirement for electrical isolation.

Sample application



Standards



Autotransformer to: VDE 0570 Teil 2-13, DIN EN 61558-2-13, EN 61558-2-13, IEC 61558-2-13, UL 5085-1/-2, CSA 22.2 No.66

Approvals



UL 5085-1/-2, CSA 22.2 No.66





Order Number

Autotransformer AT3 3,5-48/50-4

AT3 3,5-48/50-4

Type	AT3 3,5-48/50-4		Туре	AT3 3,5-48/50-4
r Input		0	Terminal and mounting	
Rated input voltage	3 x 480/500 Vac	<u>.</u>	Fixing method	Fixing rail
Rated frequency	50 - 60 Hz		Fixing screws	M6
Output		තු	Terminals	Screw-type terminals
Output Rated output voltage	3 x 400 Vac	data	Measures and weights	
Rated Power Vector group Efficiency Approvals	3500 VA	<u> </u>	Weight	8.70 kg
Vector group	YNaO	.e	Core type	3 UI 90/41,5
Efficiency	90 %			
Approvals		Mechanical		Ø _E
Approvals	cURus	Š		∠
Environment				
Ambient temperature max.	40 °C			
Safety and protection				175.0
Туре	Open type			,
Class of Insulation System	F			The state of the s
Protection index	IP 00		220.0	
Safety class (prepared)	I			`
Short circuit strength	non-short-circuit proof			
Test voltage	4000 Vac, 50 Hz			
Order numbers				





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
Autotransformer PRI 3 x 200/208 - 3 x 690 Vac, SEC 2000 - 250000 VA, 3 x 400 Vac	AT33548504	AT3 3,5-48/50-4	Buy on EAN