



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. <u>HERE</u>

Autotransformer AT3 45-20/21-4



Standards

Autotransformer to: VDE 0570 Teil 2-13, DIN EN 61558-2-13, EN 61558-2-13, IEC 61558-2-13, UL 5085-1/-2, CSA 22.2 No.66


Advantages

Low weight and small size (compared to isolating transformers)
Very high efficiency
Inverse operation possible
Patented assembly technology to lower heat losses
Very good corrosion protection and low noise thanks to $\ensuremath{BLOCKIMPEX}$ vacuum impregnation
Fixed, contact protected screw connection terminals complying with UVV BGV A3
Multifunctional fixing rails with 12 oval slots
Enlarged fixing rail for easy installation from above
late material succession

Applications

Autotransformer for adjustment of the voltage on the input and output sides with no requirement for electrical isolation.

Sample application





c SU'us

UL 5085-1/-2, CSA 22.2 No.66





Autotransformer AT3 45-20/21-4

	Туре	AT3 45-20/21-4		Туре	AT3 45-20/21-4
ያሮ			0	Terminal and mounting	
1+	Rated input voltage	3 x 200/208 Vac	က -	Fixing method	Fixing rail
	Rated frequency	50 - 60 Hz		Fixing screws	M12
data	Output		data	Terminals	Screw-type terminals
qa	Rated output voltage	3 x 400 Vac	<u>а</u>	Measures and weights	
<u>a</u>	Rated Power	45000 VA	ត្ត	Weight	197.00 kg
. <u>e</u>	Vector group	YNaO	Di	Core type	3 UI 240/140
Gt	Efficiency	97 %	ายเ		
Electrical	Approvals		Mechanical		
	Approvals	cURus	Ē		
	Environment				
	Ambient temperature max.	40 °C			510.0
	Safety and protection				
	Туре	Open type			212.0
	Class of Insulation System	F			212.0 2240.0 214.0
	Protection index	IP 00		<mark>- 550.0</mark> → 29	
	Safety class (prepared)	I. I			
	Short circuit strength	non-short-circuit proof			
	Test voltage	4000 Vac, 50 Hz			
	Order numbers				
	Order Number	AT3 45-20/21-4			







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code Reference Pro		Product link
Autotransformer PRI 3 x 200/208 - 3 x 690 Vac, SEC 2000 - 250000 VA, 3 x 400 Vac	AT34520214	AT3 45-20/21-4	Buy on EAN