



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. <u>HERE</u>

#### AT3 45-48/50-4



#### Advantages

Low weight and small size (compared to isolating transformers)

Very high efficiency

Inverse operation possible

Patented assembly technology to lower heat losses

Very good corrosion protection and low noise thanks to BLOCKIMPEX vacuum impregnation  $% \left( 1\right) =\left( 1\right) \left( 1\right) \left($ 

Fixed, contact protected screw connection terminals complying with UVV BGV  ${\sf A3}$ 

Multifunctional fixing rails with 12 oval slots


Enlarged fixing rail for easy installation from above

Integrated crane eyes

### **Applications**

Autotransformer for adjustment of the voltage on the input and output sides with no requirement for electrical isolation.

#### Sample application



#### Standards



Autotransformer to: VDE 0570 Teil 2-13, DIN EN 61558-2-13, EN 61558-2-13, IEC 61558-2-13, UL 5085-1/-2, CSA 22.2 No.66

## Approvals



UL 5085-1/-2, CSA 22.2 No.66





# Autotransformer AT3 45-48/50-4

	Туре	AT3 45-48/50-4		Туре
Electrical data 🕇	Input		0	Term
	Rated input voltage	3 x 480/500 Vac	30	Fixing r
	Rated frequency	50 - 60 Hz		Fixing s
	Output		ta	Termin
	Rated output voltage	3 x 400 Vac	_	Meas
	Rated Power	45000 VA		Weight
ج.	Vector group	YNaO	.9	Core ty
Electr	Efficiency	96 %	폘	
	Approvals		ec	
	Approvals	cURus	$\geq$	
	Environment			
	Ambient temperature max.	40 °C		
	Safety and protection			
	Туре	Open type		
	Class of Insulation System	F		
	Protection index	IP 00		
	Safety class (prepared)	T		
	Short circuit strength	non-short-circuit proof		
	Test voltage	4000 Vac, 50 Hz		
	Order numbers			
	Order Number	AT3 45-48/50-4		

	Туре	AT3 45-48/50-4
0.1	Terminal and mounting Fixing method	
~ <u></u>	Fixing method	Fixing rail
	Fixing screws	M10
ta	Terminals	Screw-type terminals
Mechanical data	Measures and weights	
g	Weight	77.30 kg
.e	Core type	3 UI 210/63
Ja		
90		
Š		









Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
Autotransformer PRI 3 x 200/208 - 3 x 690 Vac, SEC 2000 - 250000 VA, 3 x 400 Vac	AT34548504	AT3 45-48/50-4	Buy on EAN