



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. <u>HERE</u>

AT3 70-20/21-4



Advantages

Low weight and small size (compared to isolating transformers)

Very high efficiency

Inverse operation possible

Patented assembly technology to lower heat losses

Very good corrosion protection and low noise thanks to BLOCKIMPEX vacuum impregnation

Fixed, contact protected screw connection terminals complying with UVV BGV ${\sf A3}$

Multifunctional fixing rails with 12 oval slots


Enlarged fixing rail for easy installation from above

Integrated crane eyes

Applications

Autotransformer for adjustment of the voltage on the input and output sides with no requirement for electrical isolation.

Sample application



Standards



Autotransformer to: VDE 0570 Teil 2-13, DIN EN 61558-2-13, EN 61558-2-13, IEC 61558-2-13, UL 5085-1/-2, CSA 22.2 No.66

Approvals




UL 5085-1/-2, CSA 22.2 No.66





Autotransformer AT3 70-20/21-4

	Туре	AT3 70-20/21-4
Ĵ٢	Input	
1+	Rated input voltage	3 x 200/208 Vac
	Rated frequency	50 - 60 Hz
ıta	Output	
9	Rated output voltage	3 x 400 Vac
Electrical data	Rated Power	70000 VA
	Vector group	YNaO
ct	Efficiency	98 %
E	Approvals	
	Approvals	cURus
	Environment	
	Ambient temperature max.	40 °C
	Safety and protection	
	Туре	Open type
	Class of Insulation System	F
	Protection index	IP 00
	Safety class (prepared)	T .
	Short circuit strength	non-short-circuit proof
	Test voltage	4000 Vac, 50 Hz
	Order numbers	
	Order Number	AT3 70-20/21-4











Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
Autotransformer PRI 3 x 200/208 - 3 x 690 Vac, SEC 2000 - 250000 VA, 3 x 400 Vac	AT37020214	AT3 70-20/21-4	Buy on EAN