



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. <u>HERE</u>

Autotransformer AT3 70-22/23-4



Standards

Autotransformer to: VDE 0570 Teil 2-13, DIN EN 61558-2-13, EN 61558-2-13, IEC 61558-2-13, UL 5085-1/-2, CSA 22.2 No.66


Advantages

	Low weight and small size (compared to isolating transformers)
	Very high efficiency
	Inverse operation possible
	Patented assembly technology to lower heat losses
	Very good corrosion protection and low noise thanks to BLOCKIMPEX vacuum impregnation
	Fixed, contact protected screw connection terminals complying with UVV BGV A3
	Multifunctional fixing rails with 12 oval slots
	Enlarged fixing rail for easy installation from above
	Integrated crane eyes

Applications

Autotransformer for adjustment of the voltage on the input and output sides with no requirement for electrical isolation.

Sample application







UL 5085-1/-2, CSA 22.2 No.66



BLOCK Transformatoren-Elektronik GmbH • Phone +49 4231 678-0 • info@block.eu



Autotransformer AT3 70-22/23-4

Туре	AT3 70-22/23-4	Туре	AT3 70-22/23-4	
5 Input		Fixing method		
+ Rated input voltage	3 x 220/230 Vac	Fixing method	Fixing rail	
Rated frequency	50 - 60 Hz	Fixing screws	M12	
Contput Rated output voltage		rec Terminals B Measures and weights	Screw-type terminals	
Rated output voltage	3 x 400 Vac	😽 Measures and weights		
o Rated Power	70000 VA	Weight	218.00 kg	
Vector group	YNaO	Core type	3 UI 240/140	
Efficiency	97 %	IBI		
Rated Power Vector group Efficiency Approvals		Weight Core type		
Approvals	cURus			
Environment				
Ambient temperature max.	40 °C		520.0	
Safety and protection				
Туре	Open type		212.0	
Class of Insulation System	nsulation System F			
Protection index	IP 00	550.0	290.0 388	
Safety class (prepared)	I			
Short circuit strength	non-short-circuit proof			
Test voltage	4000 Vac, 50 Hz			
Order numbers				
Order numbers				







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code	Reference	Product link
Autotransformer PRI 3 x 200/208 - 3 x 690 Vac, SEC 2000 - 250000 VA, 3 x 400 Vac	AT37022234	AT3 70-22/23-4	Buy on EAN