



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. <u>HERE</u>

Autotransformer AT3 70-24/35-4



Standards

Autotransformer to: VDE 0570 Teil 2-13, DIN EN 61558-2-13, EN 61558-2-13, IEC 61558-2-13, UL 5085-1/-2, CSA 22.2 No.66


Advantages

| | Low weight and small size (compared to isolating transformers) |
|--|--|
| | Very high efficiency |
| | Inverse operation possible |
| | Patented assembly technology to lower heat losses |
| | Very good corrosion protection and low noise thanks to $\ensuremath{BLOCKIMPEX}$ vacuum impregnation |
| | Fixed, contact protected screw connection terminals complying with UVV BGV A3 $$ |
| | Multifunctional fixing rails with 12 oval slots |
| | Enlarged fixing rail for easy installation from above |
| | Integrated crane eyes |

Applications

Autotransformer for adjustment of the voltage on the input and output sides with no requirement for electrical isolation.

Sample application







UL 5085-1/-2, CSA 22.2 No.66





Autotransformer AT3 70-24/35-4

| _ | | _ | |
|---|-------------------------|--|----------------------|
| Туре | AT3 70-24/35-4 | Туре | AT3 70-24/35-4 |
| 5 Input | | Terminal and mounting | |
| + Rated input voltage | 3 x 240/346 Vac | Fixing method | Fixing rail |
| Rated frequency | 50 - 60 Hz | Fixing screws | M12 |
| B Output Rated output voltage | | Image: style="text-align: center;">Terminals Image: style="text-align: center;">Optimize: style="text-align: center;">Terminals Image: style="text-align: center;">Terminals | Screw-type terminals |
| Rated output voltage | 3 x 400 Vac | 👸 Measures and weights | |
| o Rated Power | 70000 VA | रत् Weight | 212.00 kg |
| P Vector group | YNaO | Core type | 3 UI 240/140 |
| Efficiency | 97 % | la l | |
| Rated Power Vector group Efficiency Approvals | | Weight Core type | |
| Approvals | cURus | ž – | |
| Environment | | | |
| Ambient temperature max. | 40 °C | | 520.0 |
| Safety and protection | | | |
| Туре | Open type | | |
| Class of Insulation System | F | | |
| Protection index | IP 00 | → <u>550.0</u> | 290.0 |
| Safety class (prepared) | I | | |
| Short circuit strength | non-short-circuit proof | | |
| Test voltage | 4000 Vac, 50 Hz | | |
| Order numbers | | | |
| Order Number | AT3 70-24/35-4 | | |







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

| Product | Code | Reference | e Product link | |
|---|------------|-------------------|----------------|--|
| Autotransformer PRI 3 x 200/208 - 3 x 690 Vac, SEC 2000 - 250000 VA, 3 x 400 Vac | AT37024354 | AT3 70-24/35-4 | Buy on EAN | |