



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

Mains transformer AVB 1,5/2/24



Picture shows AVB 3,2/2/18

Advantages


Minimum size at high output
Inherently short-circuit proof
Dual input voltage for series or parallel connection
Also with dual output voltage for series or parallel connection
Designed for high ambient temperatures
Permanent corrosion protection, high insulation value and maximum electrical reliability thanks to XtraDenseFill resin encapsulation
Coil shell in 2-chamber technology
Self-extinguishing potting and hood material

Applications

As a mains transformer for adjustment of the voltage and simple electrical isolation.

As a safety transformer for the safe electrical isolation of the input and output sides. The transformer is suitable for creating SELV and PELV circuits because of the limit on the output voltage.

Sample application



Standards



Mains transformer
to: VDE 0570 Teil 2-1, DIN EN 61558-2-1, EN 61558-2-1, IEC 61558-2-1, UL 5085-1/-2, CSA 22.2 No.66

Approvals



UL 5085-1/-2, CSA 22.2 No.66




Mains transformer

AVB 1,5/2/24

Type		AVB 1,5/2/24
Electrical data	Input	
	Rated input voltage	2 x 115 Vac
	Rated frequency	50 - 60 Hz
	Output	
	Rated output voltage	2 x 24 Vac
	Rated Power	1.50 VA
	No-load voltage (app. x factor)	1.39
	No-load loss (typ.)	1.00 W
	Efficiency	57 %
	Standards	
	Classification	Mains transformer
	Approvals	
	Approvals	cURus
	Environment	
	Ambient temperature max.	70 °C
	Safety and protection	
	Type	Encapsulated
	Class of Insulation System	VDE=B, UL=class 105
	Protection index	IP 00
	Safety class (prepared)	II
	Short circuit strength	inherently short-circuit proof
Order numbers		
Order Number	AVB 1,5/2/24	

Type		AVB 1,5/2/24
Mechanical data	Terminal and mounting	
	Terminals	Pins for printed circuit boards
	Pin (ø)	0.8
	Measures and weights	
	Core type	EI 30/12,5
	Weight	0.08 kg



Subjects to change.

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

Product	Code	Reference	Product link
Short circuit proof PCB transformer short circuit proof, encapsulated, PRI 2 x 115 Vac, SEC 0.35 - 3.2 VA, 2 x 6 - 2 x 24 Vac	AVB15224	AVB 1,5/2/24	Buy on EAN