



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. <u>HERE</u>

Control transformer **BUST 3000/5/23**



Advantages

High performance for the volume thanks to compact design

Primary side ± 5 % tappings for voltage adjustment


Very good corrosion protection and low noise thanks to $\mathsf{BLOCKIMPEX}$ vacuum impregnation

Contact protected screw connection terminals complying with UVV BGV A3 Low height

Applications

Control transformer for the electrical isolation of the input and output sides. The design of the transformer makes it suitable for the supply of control systems complying with VDE 0113.

Sample application





Control transformer to: VDE 0570 Teil 2-2, DIN EN 61558-2-2, EN 61558-2-2, IEC 61558-2-2, UL 5085-1/-2, CSA 22.2 No.66





UL 5085-1/-2, CSA 22.2 No.66



BLOCK Transformatoren-Elektronik GmbH • Phone +49 4231 678-0 • info@block.eu



Order Number

Control transformer **BUST 3000/5/23**

Туре	BUST 3000/5/23		
Input			
Rated input voltage	500 Vac		
Tappings Input	±5 %		
Low-inrush current	typ. rated current up to 12 times		
Rated frequency	50 - 60 Hz		
Output			
Rated output voltage	2 x 115 Vac		
Rated power VDE (DB cos phi=1)	3000 VA		
Rated power VDE (KB cos phi=0.5)	8900 VA		
Efficiency	95.3 %		
Approvals			
Approvals	cURus		
Environment			
Ambient temperature max.	40 °C		
Type of cooling	self-cooling		
Safety and protection			
Class of Insulation System	VDE=B, UL=class 130		
Protection index	IP 00		
Safety class (prepared)	1		
Туре	Open type		
ů –	non-short-circuit proof		
PRI Fusing recommendation by circuit breaker with tripping characteristic type $20\ x$ lrated related to set)			
Setting range	6.30 - 10.00 A		
Setting value	6.30 A		
Order numbers			
	Input Input Rated input voltage Tappings Input Low-inrush current Rated frequency Output Rated output voltage Rated power VDE (DB cos phi=1) Rated power VDE (KB cos phi=0.5) Efficiency Approvals Approvals Environment Ambient temperature max. Type of cooling Safety and protection Class of Insulation System Protection index Safety class (prepared) Type Short circuit strength PRI Fusing recommendation by circuit br 20 x Irated related to set) Setting range Setting value		

BUST 3000/5/23

	Туре	BUST 3000/5/23	
30	Terminal and mounting		
<u> </u>	Fixing method	Foot brackets	
	Fixing screws	M6	
ta	Terminals	Screw-type terminals	
da	Measures and weights		
a	Weight	28.00 kg	
nic			
Mechanical data			







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code	Reference	Product link
Control transformer PRI 230 - 500 Vac, SEC 1000 - 10000 VA, 24 - 2 x 115 Vac	BUST3000523	BUST 3000/5/23	Buy on EAN