



**Automatización Eléctrica**

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

Stranded copper wire on mini bobbin  
**CLI 200/60**



Picture shows CLI 200/120

## Advantages

Insulating varnish basis polyurethane, mod.

Grade 1

TJ min. 130 °C

Solderable

## Applications

Varnish insulated radio frequency copper braid for the production of coils and windings in the radio frequency range and for general laboratory needs.

## Approvals



## Stranded copper wire on mini bobbin **CLI 200/60**

Type

CLI 200/60

Type

CLI 200/60



Electrical data



Mechanical data

Operating data

Current rating 1.68 A

Environment

Heat resistance 130 °C (KLB)

insulating varnish Polyurethane, mod.

Tin-plate >350 °C

Measures and weights

Eff. cross section 0.471 mm<sup>2</sup>

Weight 0.20 kg

Subjects to change.



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

<b>Product</b>	<b>Code</b>	<b>Reference</b>	<b>Product link</b>
Stranded copper wire on mini bobbin Stranded copper wire, 200 g, Querschnitt 0,118-0,943 mm <sup>2</sup>	CLI20060	CLI 200/60	<a href="#">Buy on EAN</a>