



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

Stranded copper wire on mini bobbin **CLI 200/90**



Picture shows CLI 200/120

Advantages

Insulating varnish basis polyurethane, mod.

Grade 1

TJ min. 130 °C

Solderable

Applications

Varnish insulated radio frequency copper braid for the production of coils and windings in the radio frequency range and for general laboratory needs.

Approvals



Stranded copper wire on mini bobbin **CLI 200/90**

Type

CLI 200/90

Type

CLI 200/90



Electrical data



Mechanical data

Operating data

Current rating 2.52 A

Environment

Heat resistance 130 °C (KLB)

insulating varnish Polyurethane, mod.

Tin-plate >350 °C

Measures and weights

Eff. cross section 0.707 mm²

Weight 0.20 kg

Subjects to change.



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

Product	Code	Reference	Product link
Stranded copper wire on mini bobbin Stranded copper wire, 200 g, Querschnitt 0,118-0,943 mm ²	CLI20090	CLI 200/90	Buy on EAN