



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. <u>HERE</u>

Safety isolating transformer **EL 13/18**



Standards

Safety isolating transformer to: VDE 0570 Part 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6

 Θ

Advantages

Solder tab for free wiring

Very good corrosion protection and low noise thanks to $\ensuremath{\mathsf{BLOCKIMPEX}}$ vacuum impregnation


Coil shell in 2-chamber technology

Simple mounting thanks to robust metal footplate with oval slots

Applications

Safety isolating transformer for the safe electrical isolation of the input and output sides. The transformer is suitable for creating SELV and PELV circuits because of the limit on the output voltage.

Sample application









Safety isolating transformer **EL 13/18**

Туре	EL 13/18		Туре	EL 13/18		
5 Input		30	Terminal and mounting			
Rated input voltage	230 Vac	~	Fixing method	Base plate		
Rated frequency	50 - 60 Hz		Fixing screws	M3		
Output Rated output voltage		data	Terminals	Solder tab for free wiring		
Rated output voltage	2 x 18 Vac	qa	Measures and weights			
5 Rated Power	13.0 VA	<u>a</u>	Core type	EI 54/18,8		
2 No-load voltage (app. x factor)	1.28	.e	Weight	0.36 kg		
No-load loss (typ.)	2.20 W	Jai				
Rated Power No-load voltage (app. x factor) No-load loss (typ.) Efficiency	67 %	Mechanical				
Environment		ž				
Ambient temperature max.	40 °C					
Safety and protection						
Туре	Open type					
Class of Insulation System	E					
Protection index	IP 00			╯┘		
Safety class (prepared)	I					
Short circuit strength	non-short-circuit proof					
Overload protection	Typ PTC 872 (Accessory - available on request)					
Test voltage	4000 Vac, 50 Hz					
Order numbers						
Order Number	EL 13/18					
			45.0	30.0		

54.0



40.0





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code	Reference	Product link
Safety isolating transformer open type, for wiring, PRI 230 V, SEC 7.5 - 100 VA, 2 x 6 - 2 x 24 Vac	EL1318	EL 13/18	Buy on EAN