



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. <u>HERE</u>

Safety isolating transformer

EL 28/15



Advantages

Solder tab for free wiring

Very good corrosion protection and low noise thanks to $\ensuremath{\mathsf{BLOCKIMPEX}}$ vacuum impregnation


Coil shell in 2-chamber technology

Simple mounting thanks to robust metal footplate with oval slots

Applications

Safety isolating transformer for the safe electrical isolation of the input and output sides. The transformer is suitable for creating SELV and PELV circuits because of the limit on the output voltage.

Sample application



Standards



Safety isolating transformer to: VDE 0570 Part 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6

Approvals





Safety isolating transformer **EL 28/15**

Туре	EL 28/15		Туре	EL 28/15
Input		30	Terminal and mounting	
Rated input voltage	230 Vac	· ·	Fixing method	Base plate
Rated frequency	50 - 60 Hz		Fixing screws	M3
Output		ţa	Terminals	Solder tab for free wiring
Rated output voltage	2 x 15 Vac	data	Measures and weights	
Rated Power	28.0 VA	ō	Core type	El 60/30
No-load voltage (app. x factor)	1.16	.9	Weight	0.68 kg
No-load loss (typ.)	3.10 W	펼		
Efficiency	77 %	핞		
Environment		Mechanical		
Ambient temperature max.	40 °C			
Safety and protection				
Туре	Open type			
Class of Insulation System	E			
Protection index	IP 00			
Safety class (prepared)	II			
Short circuit strength	non-short-circuit proof			
Overload protection	Typ PTC 850 (Accessory - available on request)			
Test voltage	4000 Vac, 50 Hz			
Order numbers				
Order Number	EL 28/15			
			50.0	42.0
			60.0	56.0
			-	





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
Safety isolating transformer open type, for wiring, PRI 230 V, SEC 7.5 - 100 VA, 2 \times 6 - 2 \times 24 Vac	EL2815	EL 28/15	Buy on EAN