



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. <u>HERE</u>

EL 7,5/12



Advantages

Solder tab for free wiring

Very good corrosion protection and low noise thanks to $\ensuremath{\mathsf{BLOCKIMPEX}}$ vacuum impregnation


Coil shell in 2-chamber technology

Simple mounting thanks to robust metal footplate with oval slots

Applications

Safety isolating transformer for the safe electrical isolation of the input and output sides. The transformer is suitable for creating SELV and PELV circuits because of the limit on the output voltage.

Sample application



Standards



Safety isolating transformer to: VDE 0570 Part 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6

Approvals





Safety isolating transformer **EL 7,5/12**

| Туре | EL 7,5/12 | Туре | EL 7,5/12 |
|---------------------------------|--|---------------------------------|----------------------------------|
| Input | | Terminal and mounting | |
| Rated input voltage | 230 Vac | Fixing method | Base plate |
| Rated frequency | 50 - 60 Hz | Fixing screws | M3 |
| Output | | ♥ Terminals | Solder tab for free wiring |
| Rated output voltage | 2 x 12 Vac | Terminals Measures and weights | |
| Rated Power | 7.5 VA | Core type | El 48/16,5 |
| No-load voltage (app. x factor) | 1.38 | ·은 Weight | 0.26 kg |
| No-load loss (typ.) | 2.00 W | ie | |
| Efficiency | 62 % | Core type Weight Weight | |
| Environment | | Ž | |
| Ambient temperature max. | 40 °C | | |
| Safety and protection | | | |
| Туре | Open type | | |
| Class of Insulation System | E | | |
| Protection index | IP 00 | | ┦ [╲] ┃ ┌┈ ┃ |
| Safety class (prepared) | II | | |
| Short circuit strength | non-short-circuit proof | | |
| Overload protection | Typ PTC 880 (Accessory - available on request) | | |
| Test voltage | 4000 Vac, 50 Hz | | |
| Order numbers | | l hannonn | ┦ <u>╢╟</u> ┤ |
| Order Number | EL 7,5/12 | 0 0900090 | Ϳ <mark>ͺͺͺͺͺͺͺ</mark> ͺͺͺ |
| | | 40.0 | 32.0 |
| | | 48.0 | 39.0 |
| | | | |
| | | | |







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

| Product | Code | Reference | Product link |
|---|--------|-----------|--------------|
| Safety isolating transformer open type, for wiring, PRI 230 V, SEC 7.5 - 100 VA, 2 \times 6 - 2 \times 24 Vac | EL7512 | EL 7,5/12 | Buy on EAN |