



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. <u>HERE</u>

EP 18/12



Advantages

Minimum size at high output

Double output voltage for series or parallel connection

Very good moisture protection and low noise thanks to BLOCKIMPEX vacuum impregnation $% \left(1\right) =\left(1\right) \left(1\right) \left($

Encapsulated safety coil bodies in 2-chamber technology

Contact protected on the circuit board thanks to covered solder pin strips


Stable connection technology with injected round wire soldering pins

Additional mounting option with holes in the core

Applications

Safety isolating transformer for the safe electrical isolation of the input and output sides. The transformer is suitable for creating SELV and PELV circuits because of the limit on the output voltage.

Sample application



Standards



Safety isolating transformer to: VDE 0570 Part 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6

Approvals





Safety isolating transformer **EP 18/12**

	Туре	EP 18/12		Туре	EP 18/12
Ĵ٢	Input		0	Terminal and mounting	
1+	Rated input voltage	230 Vac	<u>ا</u> ا	Fixing method	Holes in the core package
data	Rated frequency	ency 50 - 60 Hz		Terminals	Pins for PCB
	Output		data	Measures and weights	
	Rated output voltage	2 x 12 Vac	Mechanical da	Core type	El 60/21
	Rated Power	18.0 VA		Weight	0.48 kg
Electrical	No-load voltage (app. x factor)	1.16			
ct	No-load loss (typ.)	2.70 W	뎔	3.5	→
음	Efficiency	72 %	핞		+ + + - -
	Standards		Ĭ	‡	60.0
	Classification	Safety isolating transformer		5.0	43.0
	Environment			3.0	5
	Ambient temperature max.	40 °C		10.0	4.0
	Safety and protection				50.0
	Туре	Open type		ф ф <u></u>	0.8
	Class of Insulation System	E			
	Protection index	IP 00			
	Safety class (prepared)	II			
	Short circuit strength	non-short-circuit proof			
	Overload protection	Typ PTC 860 (Accessory - available on request)			
	Order numbers				
	Order Number	EP 18/12			







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
PCB transformer open type, PRI 230 Vac, SEC 2.5 - 35 VA, 2 x 6 - 2 x 8 Vac	EP1812	EP 18/12	Buy on EAN