



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. <u>HERE</u>

EP 4,5/15



Advantages

Minimum size at high output

Double output voltage for series or parallel connection

Very good moisture protection and low noise thanks to BLOCKIMPEX vacuum impregnation $% \left(1\right) =\left(1\right) \left(1\right) \left($

Encapsulated safety coil bodies in 2-chamber technology

Contact protected on the circuit board thanks to covered solder pin strips


Stable connection technology with injected round wire soldering pins

Additional mounting option with holes in the core

Applications

Safety isolating transformer for the safe electrical isolation of the input and output sides. The transformer is suitable for creating SELV and PELV circuits because of the limit on the output voltage.

Sample application



Standards



Safety isolating transformer to: VDE 0570 Part 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6

Approvals





Safety isolating transformer **EP 4,5/15**

Type	EP 4,5/15	Туре		EP 4,5/15	
Input		Terminal and mounti	ing		
Rated input voltage	230 Vac	Fixing method		Holes in the core package	
Rated frequency	50 - 60 Hz	Terminals		Pins for PCB	
Output Rated output voltage		Measures and weigh	nts		
Rated output voltage	2 x 15 Vac	Core type		El 42/14,8	
Rated Power	4.5 VA	₹ Weight		0.16 kg	
No-load voltage (app. x factor)	1.51	.은			
No-load loss (typ.)	1.90 W	© <u>▼ 28</u>	.0		
Rated Power No-load voltage (app. x factor) No-load loss (typ.) Efficiency	56 %	Weight	+	<u> </u>	
Standards		ž Į			
Classification	Safety isolating transformer	 5		35.0	
Environment		12.5		7.5 30.0 42.0	
Ambient temperature max.	40 °C		15-1-1-1	5.0 4.0	
Safety and protection				25.0	
Туре	Open type	Φ	ф 	33.5	
Class of Insulation System	E				
Protection index	IP 00				
Safety class (prepared)	II				
Short circuit strength	non-short-circuit proof				
Overload protection	Typ PTC 890 (Accessory - available on request)				
Order numbers					
Order Number	EP 4,5/15				





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
PCB transformer open type, PRI 230 Vac, SEC 2.5 - 35 VA, 2 x 6 - 2 x 8 Vac	EP4515	EP 4,5/15	Buy on EAN