



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. <u>HERE</u>



Advantages

Integrated short circuit and overload protection

Very good moisture protection and low noise thanks to resin encapsulation

High degree of protection

Plastic fittings on terminals

Applications

Safety isolating transformer for the safe electrical isolation of the input and output sides. The transformer is suitable for creating SELV and PELV circuits because of the limit on the output voltage.

Sample application



Picture shows EVKE 250/24

Standards



Safety isolating transformer

to: VDE 0570 Part 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6

Approvals





Safety isolating transformer **EVKE 160/24**

Туре	EVKE 160/24	Туре	EVKE 160/24
S 🕝 Input	<u> </u>	Terminal and mounting	
Rated frequency	50 - 60 Hz	Fixing method	Mounting lugs
Rated input voltage	230 Vac	Terminals	Plastic fittings on 1 x M16, 1 x M20 terminals
Output Rated output voltage		Measures and weights Weight	3
Rated output voltage	24 Vac	Weight	4.50 kg
Rated Power	160 VA	<u> </u>	
은 Environment		.E	
Rated Power Environment Ambient temperature max. Safety and protection	40 °C	6.0	
Safety and protection		Mechanical	
Class of Insulation System	E	2	
Protection index	IP 68		
Safety class	II		105.0
Test voltage	3750 Vac, 50 Hz		
Туре	Resin encapsulated transformer		
Short circuit strength	non-inherently short-circuit proof	108.0	190.0
Order numbers		125.0 150.0	──
Order Number	EVKE 160/24		









Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
Safety isolating transformer encapsulated, IP 65, PRI 230 Vac, SEC 25 - 40 VA, 24 Vac	EVKE16024	EVKE 160/24	Buy on EAN