



**Automatización Eléctrica**

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

# Safety isolating transformer

## FLD 48/6



FLD 12/8


## Advantages

Minimum size at high output
Low height
Integrated overload protection using PTC in the input
Double input voltage for series or parallel connection
Double output voltage for series or parallel connection
Permanent corrosion protection, high insulation value and maximum electrical reliability thanks to XtraDensiFill resin encapsulation
Coil shell in 2-chamber technology
Self-extinguishing potting material

## Applications

As a safety isolating transformer for the safe electrical isolation of the input and output sides. The transformer is suitable for creating SELV and PELV circuits because of the limit on the output voltage.

## Sample application



## Standards

Safety isolating transformer  
to: VDE 0570 Part 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6

## Approvals



ENEC 10 (VDE)




# Safety isolating transformer FLD 48/6

Type		FLD 48/6
Electrical data	Input	
	Rated input voltage	2 x 115 Vac
	Rated frequency	50 - 60 Hz
	Output	
	Rated output voltage	2 x 6 Vac
	Rated Power	48.0 VA
	No-load voltage (app. x factor)	1.20
	No-load loss (typ.)	4.50 W
	Efficiency	79 %
	Standards	
	Classification	Safety isolating transformer
	Approvals	
	Approvals	ENEC 10 (VDE)
	Environment	
	Ambient temperature max.	40 °C
Safety and protection		
Type	Encapsulated	
Class of Insulation System	E	
Protection index	IP 00	
Safety class (prepared)	II	
Short circuit strength	non-inherently short-circuit proof	
Order numbers		
<b>Order Number</b>	<b>FLD 48/6</b>	

Type		FLD 48/6
Terminal and mounting		
Terminals		Pins for printed circuit boards
Measures and weights		
Core type		UI 48/26,0
Weight		1.02 kg

30  
Mechanical data



Subjects to change.



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

Product	Code	Reference	Product link
Short circuit proof low profile transformer short circuit proof, encapsulated, PRI 2 x 115 Vac, SEC 4 - 48 VA, 2 x 6 - 2 x 18 Vac	FLD486	FLD 48/6	<a href="#">Buy on EAN</a>