



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. <u>HERE</u>



Advantages

Minimum size at high output

Low height

Integrated overload protection using PTC in the input

Double output voltage for series or parallel connection

Permanent corrosion protection, high insulation value and maximum electrical reliability thanks to XtraDenseFill resin encapsulation


Coil shell in 2-chamber technology

Self-extinguishing potting material

Applications

As a safety isolating transformer for the safe electrical isolation of the input and output sides. The transformer is suitable for creating SELV and PELV circuits because of the limit on the output voltage.

Sample application



Standards



Safety isolating transformer to: VDE 0570 Part 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6

Approvals



ENEC 10 (VDE)





Safety isolating transformer **FLE 12/9**

	Туре	FLE 12/9		Type	FLE 12/9
Ĵ٢	Input		0	Type Terminal and mount Terminals	ting
1+	Rated input voltage	230 Vac	(1)	Terminals	Pins for PCB
	Rated frequency	50 - 60 Hz		Measures and weigh	hts
data	Output			Core type	UI 39/13,5
9	Rated output voltage	2 x 9 Vac	data	Weight	0.37 kg
Ö	Rated Power	12.0 VA	Mechanical		
.은	No-load voltage (app. x factor)	1.31	늗	□2.5	Ø 0.8 11.5
Electrical	No-load loss (typ.)	1.80 W	<u>B</u>	5.5	# 11.5
음	Efficiency	73 %		46.0	50.0
_	Standards		ž		26.0
	Classification	Safety isolating transformer		PRI S	SEC 10.0
	Approvals			↓ l	57.0
	Approvals	ENEC 10 (VDE)			
	Environment			 45 4 62	
	Ambient temperature max.	40 °C		68	.0
	Safety and protection				
	Туре	Encapsulated			
	Class of Insulation System	E			
	Protection index	IP 00			
	Safety class (prepared)	II			
	Short circuit strength	non-inherently short-circuit proof			
	Order numbers				
	Order Number	FLE 12/9			





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
Short circuit proof low profile transformer short circuit proof, encapsulated, PRI 230 Vac, SEC 4 - 48 VA, 2 x 6 - 2 x 18 Vac	FLE129	FLE 12/9	Buy on EAN