



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. <u>HERE</u>

Safety isolating transformer FLE 18/15



Advantages

Minimum size at high output

Low height

Integrated overload protection using PTC in the input

Double output voltage for series or parallel connection

Permanent corrosion protection, high insulation value and maximum electrical reliability thanks to XtraDenseFill resin encapsulation


Coil shell in 2-chamber technology

Self-extinguishing potting material

Applications

As a safety isolating transformer for the safe electrical isolation of the input and output sides. The transformer is suitable for creating SELV and PELV circuits because of the limit on the output voltage.

Sample application



Standards

Safety isolating transformer to: VDE 0570 Part 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6






ENEC 10 (VDE)





Safety isolating transformer **FLE 18/15**

	Туре	FLE 18/15		Туре
tа +I	Input		30	Terminal
	Rated input voltage	230 Vac		Terminals
	Rated frequency	50 - 60 Hz		Measures
	Output		data	Core type
qa	Rated output voltage	2 x 15 Vac	<u>р</u>	Weight
a	Rated Power	18.0 VA	<u>a</u>	
Electrical data	No-load voltage (app. x factor)	1.30	Mechanical	
	No-load loss (typ.)	2.00 W		5.5
	Efficiency	75 %		46.0
	Standards		Ξ	
	Classification	Safety isolating transformer		
	Approvals			Ļ
	Approvals	ENEC 10 (VDE)		-
	Environment			
	Ambient temperature max.	40 °C		
	Safety and protection			
	Туре	Encapsulated		
	Class of Insulation System	E		
	Protection index	IP 00		
	Safety class (prepared)	II		
	Short circuit strength	non-inherently short-circuit proof		
	Order numbers			
	Order Number	FLE 18/15		









Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code	Reference	Product link
Short circuit proof low profile transformer short circuit proof, encapsulated, PRI 230 Vac, SEC 4 - 48 VA, 2 x 6 - 2 x 18 Vac	FLE1815	FLE 18/15	Buy on EAN