



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. <u>HERE</u>



Advantages

Minimum size at high output

Low height

Integrated overload protection using PTC in the input

Double output voltage for series or parallel connection

Permanent corrosion protection, high insulation value and maximum electrical reliability thanks to XtraDenseFill resin encapsulation


Coil shell in 2-chamber technology

Self-extinguishing potting material

Applications

As a safety isolating transformer for the safe electrical isolation of the input and output sides. The transformer is suitable for creating SELV and PELV circuits because of the limit on the output voltage.

Sample application



Standards



Safety isolating transformer to: VDE 0570 Part 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6

Approvals



ENEC 10 (VDE)





Safety isolating transformer **FLE 4/6**

Type	_	FLE 4/6		Type	FLE 4/6
լ 🕝 Input	Input			Terminal and mour Terminals	nting
	put voltage	230 Vac	<u></u>	Terminals	Pins for PCB
Rated fr	requency	50 - 60 Hz		Measures and wei	
Output Rated ou	ut		data	Core type	UI 30/10,5
Rated or	utput voltage	2 x 6 Vac	9	Weight	0.18 kg
Rated Po	ower	4.0 VA	<u></u>		
-은 No-load	voltage (app. x factor)	1.37	.e	4.5	Ø0.8 9.0
No-load No-load	loss (typ.)	0.80 W	Mechanical		9.0 9.0 9.0 9.0 9.0 9.0 9.0 9.0 9.0 9.0
Efficiency	у	70 %	99	35.0	37.5
	Standards				25.0
Classific	ation	Safety isolating transformer		PRI	SEC 5.0
Approv	vals				44.0
Approval	ls	ENEC 10 (VDE)		* 	
Enviror	Environment				5.0 7.5
Ambient	temperature max.	40 °C		5	3.0
Safety	and protection				
Туре		Encapsulated			
Class of	Class of Insulation System E				
Protection	on index	IP 00			
Safety cl	lass (prepared)	II			
Short cir	rcuit strength	non-inherently short-circuit proof			
Order	numbers				
Order N	lumber	FLE 4/6			







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
Short circuit proof low profile transformer short circuit proof, encapsulated, PRI 230 Vac, SEC 4 - 48 VA, 2 x 6 - 2 x 18 Vac	FLE46	FLE 4/6	Buy on EAN