



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)




Safety isolating transformer FLN 14/15

Type		FLN 14/15
Electrical data	Not for new designs Alternative type FL 14/15	
	Input	
	Rated input voltage	2 x 115 Vac
	Rated frequency	50 - 60 Hz
	Output	
	Rated output voltage	2 x 15 Vac
	Rated Power	14.0 VA
	No-load voltage (app. x factor)	1.38
	No-load loss (typ.)	2.00 W
	Efficiency	67 %
Standards		
Classification	Safety isolating transformer	
Approvals		
Approvals	cURus, ENEC 10 (VDE)	
Environment		
Ambient temperature max.	70 °C	
Safety and protection		
Type	Encapsulated	
Class of Insulation System	B	
Protection index	IP 00	
Safety class (prepared)	II	
Short circuit strength	non-short-circuit proof	
Order numbers		
Order Number	FLN 14/15	

Type		FLN 14/15
Terminal and mounting		
Terminals	Pins for PCB	
Measures and weights		
Core type	UI 39/10,2	
Weight	0.34 kg	

30
Mechanical data



Subjects to change.



Automatización Eléctrica
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

Product	Code	Reference	Product link
Low profile transformer Discontinued model, alternative type FL	FLN1415	FLN 14/15	Buy on EAN