



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

Line reactor, single-phase **NKE 20/2,55**



Picture shows NKE 25/2,04

Advantages

Use as line reactor, commutating reactor or PFC reactor
Power harmonic damping
Starting current limitation
Increases the service life of consumers
Low ripple
Very good corrosion protection and low noise thanks to BLOCKIMPEX vacuum impregnation
Bridging voltage dips
Peak current limitation

Applications

Line reactor to minimise mains pollution, to reduce the reactive-power components and charging currents in the DC link capacitor and to improve the $\cos(\phi)$.

Standards

Line- and commutation reactor to
DIN EN 61558-2-20, IEC 61558-2-20, UL 506, CSA 22.2

Approvals


UL 506, CSA 22.2



Line reactor, single-phase NKE 20/2,55

Type		NKE 20/2,55
Electrical data	Operating data	
	Rated voltage	400 Vac
	Voltage drop	16 Vac
	Rated current	20 A
	Rated frequency	50 - 60 Hz
	Inductivity	2.550 mH
	Inductivity deviation	±10%
	Approvals	
	Approvals	cURus
	Environment	
	Ambient temperature	-10 °C to +40 °C
	Type of cooling	AN
	Safety and protection	
	Class of Insulation System	B
	Protection index	IP 00
Safety class (prepared)	I	
Type	Open type	
Test voltage	2500 Vac	
Order numbers		
Order Number	NKE 20/2,55	

Type		NKE 20/2,55
Mechanical data	Terminal and mounting	
	Terminals phase	Screw clamp, 10 mm ²
	Terminals PE	Tab connector, 6.3 x 0.8 mm
	Fixing method	Base plate
	Fixing screws	M5
	Measures and weights	
	Weight	4.20 kg





Automatización Eléctrica
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

Product	Code	Reference	Product link
Line reactor, single-phase 230 or 400 Vac, 4- 25 A, Short circuit voltage (uK): 4%	NKE20255	NKE 20/2,55	Buy on EAN