



**Automatización Eléctrica**

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

# Isolating transformer RKD 1600/2x115



Picture shows RKD 60 2x12

## Advantages

Minimum size at high power
Low weight
Double input voltage for series or parallel connection
Minimal no-load losses
Outstanding temperature behaviour thanks to low magnetic leakage field
Very low noise field


## Applications

As a mains transformer for adjustment of the voltage and simple electrical isolation.

As an isolating transformer for the safe electrical isolation of the input and output sides. The transformer may be used to set up protective separation as a protective measure in accordance with VDE 0100.

As a safety isolating transformer for the safe electrical isolation of the input and output sides. The transformer is suitable for creating SELV and PELV circuits because of the limit on the output voltage.

## Sample application



## Standards




Isolating transformer  
 to: VDE 0570 Part2-4, DIN EN 61558-2-4, EN 61558-2-4, IEC 61558-2-4, UL 5085-1/-2, CSA 22.2 No.66

## Approvals



UL 5085-1/-2, CSA 22.2 No.66



# Isolating transformer

## RKD 1600/2x115

Type		RKD 1600/2x115
Electrical data	Input	
	Rated input voltage	2x115 Vac
	Rated frequency	50 - 60 Hz
	Output	
	Rated output voltage	2 x 115 Vac
	Rated Power	1600 VA
	No-load voltage (app. x factor)	1.02
	No-load loss (typ.)	9.60 W
	Efficiency	97 %
	Standards	
	Classification	Isolating transformer
	Approvals	
	Approvals	cURus
	Environment	
	Ambient temperature max.	40 °C
	Safety and protection	
	Type	Open type
	Class of Insulation System	VDE=B, UL=class 105
	Protection index	IP 00
	Safety class (prepared)	II
Short circuit strength	non-short-circuit proof	
Test voltage	4000 Vac, 50 Hz	
Order numbers		
<b>Order Number</b>	<b>RKD 1600/2x115</b>	

Type		RKD 1600/2x115
Mechanical data	Terminal and mounting	
	Fixing method	Remaining hole casting, with integrated mounting holes
	Terminals	Connecting leads, 200 mm
	Measures and weights	
	Major diameter Ø	202 mm
	Outside diameter in the area of the wire lead Ø	205 mm
	Height without mounting	105 mm
	Weight	12.70 kg

Subjects to change.



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
Toroidal safety isolating and isolating transformer PRI 2 x 115 Vac, SEC 15 - 3000 VA, 2 x 12 - 2 x 115 Vac	RKD16002x115	RKD 1600/2x115	<a href="#">Buy on EAN</a>