



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. <u>HERE</u>

Safety isolating transformer

SIM 500



Advantages

Integrated short circuit and overload protection

Double output voltage for series or parallel connection


Very good moisture protection and low noise thanks to XtraDenseFill resin encapsulation (up to 300 VA) $\,$

Screw terminals under cover with strain relief

Applications

Safety isolating transformer for the safe electrical isolation of the input and output sides. The transformer is suitable for creating SELV and PELV circuits because of the limit on the output voltage.

Sample application



Standards



Safety isolating transformer to: VDE 0570 Part 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6 **Approvals**






VDE





Safety isolating transformer **SIM 500**

Туре	SIM 500		Type
Input		0	Terminal and mount
Rated frequency	50 - 60 Hz	<u>ا</u> ا	Fixing method
Rated input voltage	230 Vac		Terminals
Output		ta	Measures and weig
Rated output voltage	2 x 12 Vac	6	Weight
Rated Power	500 VA	o	
No-load voltage (app. x factor)	1.04	.e	<u> </u>
No-load loss (typ.)	18.00 W	ы	
Efficiency	92 %	5	
Standards		ğ	
Classification	Safety isolating transformer		م آ
Approvals			283.0
Approvals	VDE, cURus		
Environment			
Ambient temperature max.	40 °C		
Safety and protection			
Туре	Encapsulated in metal housing		
Class of Insulation System	В		
Protection index	IP 20		
Safety class	1		
Short circuit strength	non-inherently short-circuit proof		
Test voltage	3750 Vac, 50 Hz		
Order numbers			
Order Number	SIM 500		
	Input Rated frequency Rated input voltage Output Rated output voltage Rated Power No-load voltage (app. x factor) No-load loss (typ.) Efficiency Standards Classification Approvals Approvals Environment Ambient temperature max. Safety and protection Type Class of Insulation System Protection index Safety class Short circuit strength Test voltage Order numbers	Input Rated frequency Rated input voltage Output Rated output voltage 2 x 12 Vac Rated Power No-load voltage (app. x factor) No-load loss (typ.) Efficiency Standards Classification Approvals Approvals Environment Ambient temperature max. Safety and protection Type Class of Insulation System B Protection index Safety class I Short circuit strength Test voltage Order numbers	Input Rated frequency Rated input voltage 230 Vac Output Rated output voltage 2 x 12 Vac Rated output voltage Rated Power Ro-load voltage (app. x factor) No-load loss (typ.) 18.00 W Efficiency 92 % Standards Classification Approvals Approvals Environment Ambient temperature max. Ambient temperature max. Safety and protection Type Class of Insulation System B Protection index IP 20 Safety class I Short circuit strength non-inherently short-circuit proof Test voltage Order numbers







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
Safety isolating transformer encapsulated, PRI 230 Vac, SEC 60 - 800 VA, 2 x 12 Vac	SIM500	SIM 500	Buy on EAN