



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. <u>HERE</u>



Advantages

Safe galvanic isolation

Integrated short circuit and overload protection

Double output voltage for series or parallel connection


Very good moisture protection and low noise thanks to XtraDenseFill resin encapsulation (up to $300\ VA$)

Screw terminals under cover with strain relief

Applications

Isolating transformer for the safe electrical isolation of the input and output sides. The transformer may be used to set up protective separation as a protective measure in accordance with VDE 0100.

Sample application



Standards



Isolating transformer to: VDE 0570 Part 2-4, DIN EN 61558-2-4, EN 61558-2-4, IEC 61558-2-4

Approvals




VDE





Isolating transformer **TIM 60**

Туре	TIM 60
3 € Input	
Rated frequency	50 - 60 Hz
Rated input voltage	230 Vac
으 Output	
Gutput Rated output voltage Rated Power No-load voltage (app. x factor) No-load loss (typ.) Efficiency	2 x 115 Vac
Rated Power	60 VA
- No-load voltage (app. x factor)	1.15
No-load loss (typ.)	3.30 W
Efficiency	83.5 %
Approvals	
Approvals	VDE
Environment	
Ambient temperature max.	40 °C
Safety and protection	
Туре	Resin encapsulated transformer
Class of Insulation System	A
Protection index	IP 20
Safety class	II .
Short circuit strength	non-inherently short-circuit proof
Test voltage	5000 Vac, 50 Hz
Order numbers	
Order Number	TIM 60







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
Isolating transformer encapsulated, PRI 230 Vac, SEC 60 - 1000 VA, 2 \times 115 Vac	TIM60	TIM 60	Buy on EAN