



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. <u>HERE</u>



Advantages

Minimum size at high output

Inherently short-circuit proof

Also with dual output voltage for series or parallel connection

Designed for high ambient temperatures

Permanent corrosion protection, high insulation value and maximum electrical reliability thanks to XtraDenseFill resin encapsulation

Coil shell in 2-chamber technology


Self-extinguishing potting material

Applications

As a mains transformer for adjustment of the voltage and simple electrical isolation

As a safety isolating transformer for the safe electrical isolation of the input and output sides. The transformer is suitable for creating SELV and PELV circuits because of the limit on the output voltage.

Sample application



Standards

Mains transformer to: VDE 0570 Teil 2-1, DIN EN 61558-2-1, EN 61558-2-1, IEC 61558-2-1, UL 5085-1/-2, CSA 22.2 No.66

Approvals



UL 5085-1/-2, CSA 22.2 No.66





Mains transformer **VB 1,5/2/15**

	Туре	VB 1,5/2/15		Туре	VB 1,5/2/15
Electrical data +	Input		data	Type Terminal and mounting Terminals	
	Rated input voltage	230 Vac		Terminals	Pins for printed circuit boards
	Rated frequency	50 - 60 Hz		Measures and weights	
	Output			Pin (ø)	0.8 mm
	Rated output voltage	2 x 15 Vac		Core type	EI 30/12,5
	Rated Power	1.50 VA	<u></u>	Weight	0.08 kg
	No-load voltage (app. x factor)	1.45	Mechanical		
	No-load loss (typ.)	1.00 W		□ 20.0	
	Efficiency	57 %		5.0	
	Standards		Š		
	Classification	Mains transformer			
	Approvals			20.0	32.3
	Approvals	cURus		5.0	
	Environment				T T
	Ambient temperature max.	70 °C			_
	Safety and protection			27.3 →	
	Туре	Encapsulated			
	Class of Insulation System	VDE=B, UL=class 105			
	Protection index	IP 00			
	Safety class (prepared)	II .			
	Short circuit strength	inherently short-circuit proof			
	Order numbers				
	Order Number	VB 1,5/2/15			







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
Short circuit proof PCB transformer short circuit proof, encapsulated, PRI 230 Vac, SEC 0.35 - 3.2 VA, 6 - 24 Vac, 2 x 6 - 2 x 24 Vac	VB15215	VB 1,5/2/15	Buy on EAN