



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. <u>HERE</u>



Advantages

Minimum size at high output

Also with double output voltage for series or parallel connection

Designed for high ambient temperatures

Permanent corrosion protection, high insulation value and maximum electrical reliability thanks to XtraDenseFill resin encapsulation

Coil shell in 2-chamber technology

Self-extinguishing potting material


Additional mounting option with tabs on the housing (from 28 VA)

Applications

As a mains transformer for adjustment of the voltage and simple electrical

As a safety isolating transformer for the safe electrical isolation of the input and output sides. The transformer is suitable for creating SELV and PELV circuits because of the limit on the output voltage.

Sample application



Standards



Safety isolating transformer to: VDE 0570 Part 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6, UL 5085-1/-2, CSA 22.2 No.66

Approvals









Safety isolating transformer **VCN 50/1/7,5**

Туре	VCN 50/1/7,5		Туре	VCN 50/1/7,5
Input	<u> </u>	0	l ype Terminal and mounting Terminals	
Rated input voltage	230 Vac	<u> </u>	Terminals	Pins for printed circuit boards
Rated frequency	50 - 60 Hz		Measures and weights	
Output Rated output voltage		data	Pin (ø)	0.8 mm
Rated output voltage	7.5 Vac	da	Core type	El 66/34,5
	50.0 VA	<u></u>	Weight	1.07 kg
No-load voltage (app. x factor)	1.13	.e		
No-load loss (typ.)	4.80 W	ie i		
Rated Power No-load voltage (app. x factor) No-load loss (typ.) Efficiency	84 %	Mechanical		
Standards		ž		
Classification	Safety isolating transformer			
Approvals				
Approvals	cURus, ENEC 10 (VDE)			
Environment				
Ambient temperature max.	70 °C			
Safety and protection				
Туре	Encapsulated			
Class of Insulation System	В			
Protection index	IP 00			
Safety class (prepared)	II .			
Short circuit strength	non-short-circuit proof			
Order numbers				
Order Number	VCN 50/1/7,5			







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
PCB transformer encapsulated, PRI 230 Vac, SEC 3.2 - 16 VA, 6 - 24 Vac, 2 x 6 - 2 x 24 Vac	VCN50175	VCN 50/1/7,5	Buy on EAN