



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. <u>HERE</u>



Advantages

Minimum size at high output

Also with double output voltage for series or parallel connection

Designed for high ambient temperatures

Permanent corrosion protection, high insulation value and maximum electrical reliability thanks to XtraDenseFill resin encapsulation

Coil shell in 2-chamber technology

Self-extinguishing potting material


Additional mounting option with tabs on the housing (from 28 VA)

Applications

As a mains transformer for adjustment of the voltage and simple electrical

As a safety isolating transformer for the safe electrical isolation of the input and output sides. The transformer is suitable for creating SELV and PELV circuits because of the limit on the output voltage.

Sample application



Standards



Safety isolating transformer to: VDE 0570 Part 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6, UL 5085-1/-2, CSA 22.2 No.66

Approvals










Safety isolating transformer **VCN 6/2/12**

Туре	VCN 6/2/12		
, F Input			
Rated input voltage	230 Vac		
Rated frequency	50 - 60 Hz		
Output Rated output voltage Rated Power No-load voltage (app. x factor) No-load loss (typ.) Efficiency			
Rated output voltage	12.0 Vac		
Rated Power	6.0 VA		
- No-load voltage (app. x factor)	1.46		
No-load loss (typ.)	2.00 W		
Efficiency	63 %		
Standards			
Classification	Safety isolating transformer		
Approvals			
Approvals	cURus, ENEC 10 (VDE)		
Environment			
Ambient temperature max.	70 °C		
Safety and protection			
Туре	Encapsulated		
Class of Insulation System	В		
Protection index	IP 00		
Safety class (prepared)	II		
Short circuit strength	non-short-circuit proof		
Order numbers			
Order Number	VCN 6/2/12		







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
PCB transformer encapsulated, PRI 230 Vac, SEC 3.2 - 16 VA, 6 - 24 Vac, 2 x 6 - 2 x 24 Vac	VCN6212	VCN 6/2/12	Buy on EAN