At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. HERE

Conductive Sensors
Level Probes
Types VN, VNY, VPC, VPP



- 1 to 4 electrodes
- Isolated or unisolated electrodes
- Cable or screw connection
- 1/2", 1" or 1 1/2" without pipe thread according to ISO 228/1-Gxxx"

CE

Product Description

Level sensor for measuring the level of conductive liquids, i.e. max./min. control of charging or discharging. The function is determined by the amplifier relay used. The sensors are delivered with standard length electrodes - these are cut off to suit the application.

Ordering Key

VPC 110

Type
Housing material
Number of electrodes
Thread

Type Selection

Pipe thread	Electrode isolation	Housing Material	Ordering no. 1 electrode	Ordering no. 2 electrodes	Ordering no. 3 electrodes	Ordering no. 4 electrodes
1 1/2"	No	Nylon 6	**VN 1**	**VN 2**	**VN 3**	**VN 4**
1 1/2"	No	Nylon 6	**VNY 1**	**VNY 2**	**VNY 3**	**VNY 4**
1 1/2"	Polyethylene	Nylon 6	**VNI 1**	**VNI 2**	**VNI 3**	**VNI 4**
1 1/2"	Polyethylene	Nylon 6	**VNYI 1**	**VNYI 2**	**VNYI 3**	**VNYI 4**
1/2"	Polyethylene	PVC	**VPC 105**	**VPC 205**		
1"	Polyethylene	PVC	**VPC 110**	**VPC 210**	**VPC 310**	
1/2"	Kynar (PVDF)	Polypropylene	**VPP 105**	**VPP 205**		
1"	Kynar (PVDF)	Polypropylene	**VPP 110**	**VPP 210**	**VPP 310**	

Specifications

Electrodes	
Material	Stainless steel AISI316/DIN1.4401
Standard length	
VN, VNY	100 cm
VPC, VPP	50 cm
Diameter	
VN, VNY	Ø 5 mm
VPC, VPP	Ø 4 mm
Housing	
Connection	
VN	Cable (PVC), 2 m
VNY, VPC, VPP	Screw terminals

Environment	
Degree of protection	IP 67
Operating temperature	
VN, VNY	0 to 90°C (32° to 194 °F)
VPC	0 to 60°C (32° to 140 °F)
VPP	0 to 100°C (32° to 212 °F)
Storage temperature	
VN, VNY	-25° to 100°C (-13° to 212°F)
VPC, VPP	-20° to 110°C (-40° to 230°F)
Pressure	
VN, VNY, VPP	10 bar at 60°C
VPC	2 bar at 60°C
CE marking	IEC 529

Mode of Operation

The length of the electrodes determines the levels which will be detected and the amplifier chosen determines the function (see SV..., S195/196, S1961, ELA, ELC or ELD). If the container is made of a conductive material this can be used as common electrode.

Accessories

Extension joint for Ø5 mm electrodes (VN/VNI): **VD1**

Dimensions



VN



VNY



VPC05, VPP05



VPC10, VPP10

Wiring Diagrams



VN/VNI 1 **VN/VNI 2** **VN/VNI 3** **VN/VNI 4**

Automatización Eléctrica
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
Selected parameters SYSTEM Sensor HOUSING 1" pipe thread iso 228/1G SENSING FUNCTION 1 Electrode CONNECTION Terminals, PG9 MATERIAL Plastic Others SENSING FUNCTION 1 m MATERIAL PVC ADDITIONAL Polyethylene	VPC110		Buy on EAN