



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. [HERE](#)

HT 131-C

This new model, self contained, robust and sturdy, will accept all semi-circular slotted dies, common to most 130 kN tools. The tool features a double speed action: a fast advancing speed for rapid approach of the dies to the connector and a slower more powerful speed for crimping. For ease of operation and comfort of the operator the tool head can be fully rotated through 180 degrees.

HYDRAULIC CRIMPING TOOL

general features

Crimping force kN	Dimensions mm		Jaw Opening mm	Weight kg
	length	width		
130	473	144	25	5,5

MAIN APPLICATIONS - max section mm²

L.V. lugs and splices	Insulated terminals	"C" sleeve Connectors	H.V. lugs	H.V. Splices
400	240	185	400	400*

* limited to the cable insulation diameter

STORAGE

Type	Dimensions mm	Weight kg	Supplied with the tool	Purchase separately
VAL P3*	620x380x135	2,5	✱	—

*Suitable for storage of the tool and 14 sets of dies

The built-in safety valve will by-pass the oil supply when the maximum pressure is reached, and the pressure release system can easily be operated at any stage of compression.



RHC 131

Hydraulic presshead complete with quick automatic coupler for connection to a hydraulic pump with a working pressure of 700 bar max, (see page 172-176) **This new design with improved mechanical features,**

HYDRAULIC PRESSHEADS

general features



Crimping force kN	Max operating pressure bar	Dimensions mm		Jaw Opening mm	Weight kg
		length	width		
130	700	232	124	25	3,8

MAIN APPLICATIONS - max section mm²

L.V. lugs and splices	Insulated terminals	"C" sleeve Connectors	H.V. lugs	H.V. Splices
400	240	185	400	400*

* limited to the cable insulation diameter

STORAGE

Type	Dimensions mm	Weight kg	Supplied with the tool	Purchase separately
VAL P26*	445x290x115	1,2	—	✱

*Suitable for storage of the head and 14 sets of dies

is suitable for installing the same range of connectors as HT 131-C.



RHM 132

Hydraulic press-head complete with quick automatic coupler for connection to a hydraulic pump with a working pressure of 700 bar max, (see page 172-176).

general features

Crimping force kN	Max operating pressure bar	Dimensions mm		Weight kg
		length	width	
130	700	216	80	3,1

Particularly suitable for high volume bench crimping.

MAIN APPLICATIONS - max section mm²

L.V. lugs	Insulated terminals	H.V. lugs
400	240	400

STORAGE

Type	Dimensions mm	Weight kg	Supplied with the tool	Purchase separately
VAL P26*	445x290x115	1,2	—	✱

*Suitable for storage of the head and 14 sets of dies



These tools are supplied without dies. For die selection, please refer to chart on pages 196 to 205

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
TAG MG-TPM 40040 (4X10 YE)	4101120	40040	Buy on EAN
VAL P3 CARRYING CASE (HT81/120)	2590610	VAL-P3	Buy on EAN
RHM132 PRESSHEAD	2619410	RHM-132	Buy on EAN
RHC131 PRESSHEAD	2619010	RHC131	Buy on EAN
VAL P26 CARRYING CASE	2590635	VAL-P26	Buy on EAN
2176 MECHANICAL FIXING LUG	3051430	2176	Buy on EAN
HT131-C CRIMPING TOOL	2610416	HT131-C	Buy on EAN