



Automatzación Eléctrica
Especialistas en Automatzación

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. [HERE](#)



HYDRAULIC CUTTING HEAD

general features

INDUSTRIAL APPLICATION TC 120

Max cutting Ø mm	Max operating pressure bar	Dimensions mm		Weight kg
		length	width	
120	700	536	175	9,5

STORAGE

Type	Dimensions mm	Weight kg	Supplied with the tool	Purchase separately
VAL TC 120	590x209xh84	4,9	✱	—



Hydraulic cutting head specifically designed to cut Copper, Aluminium and Telecommunications cable having a max overall diameter of 120 mm.

The head can easily be opened to cut running cables, and the handle allows the most comfortable positioning of the head onto the cable to be cut.

The head is complete with a quick automatic coupler for connection to a hydraulic pump with a working pressure of 700 bar max, (see page 172-176).

TC 120 cutting capacity - a few examples:	
Cable type	3x150 mm ² Steel armoured Ø80 mm
	1000 mm ² Cu - EPR rubber insulated; Ø85 mm
	1000 mm ² Cu - EPR rubber insulated + lead sheath; Ø92 mm
	1000 mm ² Cu - EPR rubber insulated + lead sheath + PE sheath; Ø100 mm
	240 mm ² EPR rubber insulated



Handle designed for ease of operation



Opening head, to allow cutting of running cables

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

Product	Code	Reference	Product link
TC120 CUTTER HEAD	2597250	TC-120	Buy on EAN