Reference: 017-522966
Code: 017522966

Type Code RT124 , Weight 0.968 Kg , Ambient temp. -50 - 70 °C , Ambient temp. -58 - 158 °F , Approval CCC

Buy it at Electric Automation Network

RT thermostats are used in general industrial and marine sectors. The RT thermostats series consist of a variety of ordinary room temperature switches and remote sensor temperature switches including neutral zone temperature switches. RT thermostats are generally recommended for applications where safety or economical consequences are critical factors. RT thermostats have been in service for more than 60 years. Temperature ranges: - 60°C to 300°C Replaceable contact system Also available with gold plated contact systems Fail-safe Adjustable differential Enclosure IP66 Available with min. and max. reset function (IP54) Available with dead zone Available with all relevant marine approvals

Type Code	RT124
Weight	0.968 Kg
Ambient temp.	-50 - 70 °C
Ambient temp.	-58 - 158 °F
Approval	CCC, CE, DNV, EAC, NKK, RINA
Cap. tube length	196 7/8 in
Cap. tube length	5.000 mm
Charge type	Partial
Contact function	SPDT
Contact rating	AC1=10 A, 400 V
Contact rating	AC15=3 A, 400 V
Contact rating	AC3=4 A, 400 V
Contact rating	DC13=12 W, 220 V
Contact rating	LR=28 A, 400 V

Diff. max. range setting	2,5 - 10,0 °C
Diff. min. range setting	5,0 - 25,0 °C
Diff. type	Adjustable
EAN no.	5702423120864

Electr. conn. size	2xPg 13.5
Electr. spec. standard	EN 60947-4/-5
Encl.	IP66
Glow lamp	No
Max. sensor temp.	350 °C
Max. sensor temp.	662,0 °F
Prod. description	Temperature Control
Prod. group	Switches and thermostats
Prod. name	Thermostat
Reset	AUTO
Sensor size (ø x L)	7/16 x 4 1/4 in
Sensor size (ø x L)	11 x 110 mm
Sensor type	Remote Sensor
Temp. range	200 - 300 °C
Temp. range	392 - 572 °F