Danfoss Automation

EA Electric Automation
Automation specialists

Reference: 032H8039

Type Code EV210A , Weight 0.139 Kg , Actuator size 9 mm , Actuator size 0.35 in , Ambient temp. max. 50 °C

Buy it at Electric Automation Network

EV210A covers a wide range of small, direct-operated 2/2-way solenoid valves for use in industrial machinery. The compact design together with the broad range of coils means that EV210A covers a broad variety of industrial applications.

Type Code	EV210A
Weight	0.139 Kg
Actuator size	9 mm
Actuator size	0.35 in
Ambient temp. max.	50 °C
Ambient temp. max.	122 °F
Body mat.	Stainless steel
Connection	G 1/4
Conn. Int./Ext.	Internal
Conn. std.	ISO 228-1
Cv value	0,200 gpm US
Diff. pressure	0 - 20 bar
Diff. pressure	0,0 - 285,7 psi
EAN no.	5702423050901

Function	N C
Kv value	0,170 m3/h
Max. Working Pressure	50,0 bar

Max. Working Pressure	715 psig
Medium temp. range	-10 - 100 °C
Medium temp. range	15 - 210 °F
Number of ways	2/2
Operation	Direct-operated
Orifice size	2,50 mm
Orifice size	3/32 in
Seal mat.	FKM
Type designation	Solenoid valve