



Electric Automation
Automation specialists

Reference: 042N0156

Type Code Spare part , Weight 0.034 Kg , Ambient temp. range -40 - 80 °C , Ambient temp. range -40 - 176 °F , Approval CE

Buy it at Electric Automation Network



Accessories and spare parts for EVU solenoid valves

Type Code	Spare part
Weight	0.034 Kg
Ambient temp. range	-40 - 80 °C
Ambient temp. range	-40 - 176 °F
Approval	CE
Body mat.	PA6 + 30% GF
Body type	Opaque
Cable diam.	0,24 - 0,35 in
Cable diam.	6,0 - 9,0 mm
Cable holder mat.	PA6
Conductor size, max.	1,5 mm ²
Contact mat.	CuZn (Cu/Sn plated)
Cont. resist. max.	4 mOhm
Contacts	2 + PE
EAN no.	5702423012183
Electr. conn. form	Form A

Electr. conn. size	PG 11
Electr. conn. standard	EN 175301-803
Encl.	IP65
Gasket mat.	NBR
Gasket type	Profiled
Operat. current max.	16,0 A
Supply volt. AC	250 V

Supply volt. DC	250,00 V
Terminal block mat.	PA6 + 30% GF
Type design.	Cable plug
Used for	018F Coil Type B
Used for	018Z Coil Type B
Used for	042N Coil Type B