



**Circuit-breaker, 4 p, 160A**

**Part no. LZMB1-4-ASF160-I**  
**Article no. 111867**

Similar to illustration

**Technical data ETIM 6.0**

|  |    |  |
|--|----|--|
| Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation prot. (EC000228)   |    |  |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection (ecl@ss8.1-27-37-04-09 [AJZ716010]) |    |  |
| Rated permanent current I <sub>u</sub>   | A  | 160                                      |
| Rated voltage  | V  | 690 - 690                                |
| Rated short-circuit breaking capacity I <sub>cu</sub> at 400 V, 50 Hz  | kA | 25                                       |
| Overload release current setting   | A  | 125 - 160                                |
| Adjustment range short-term delayed short-circuit release  | A  | 0 - 0                                    |
| Adjustment range undelayed short-circuit release   | A  | 960 - 1600                               |
| Integrated earth fault protection  |    | No                                       |
| Type of electrical connection of main circuit  |    | Frame clamp                              |
| Device construction  |    | Built-in device fixed built-in technique |
| Suitable for DIN rail (top hat rail) mounting  |    | No                                       |
| DIN rail (top hat rail) mounting optional  |    | Yes                                      |
| Number of auxiliary contacts as normally closed contact  |    | 0  |
| Number of auxiliary contacts as normally open contact  |    | 0  |
| Number of auxiliary contacts as change-over contact  |    | 0  |
| Switched-off indicator available   |    | No                                       |
| With under voltage release   |    | No                                       |
| Number of poles  |    | 4  |
| Position of connection for main current circuit  |    | Front side                               |
| Type of control element  |    | Rocker lever                             |
| Complete device with protection unit   |    | Yes                                      |
| Motor drive integrated   |    | No                                       |
| Motor drive optional   |    | No                                       |
| Degree of protection (IP)  |    | IP20                                     |