









Circuit-Breakers

Circuit Breakers, thermomagnetic releases, 3- and 4-pole

NZM

		Switching capacity 400/415V 50/60 Hz I_{cu} kA	Rated current = Rated uninterrupted current $I_n = I_u$ A	Setting range Overload release I_r A 	Setting range Short-circuit release Non-delayed $I_i = I_n \times \dots$ 	Part no. Article no.
System and Cable Protection						
Comfort switching capacity						
	3-pole	36	320	250-320	6-10	NZMC3-A320-SVE 168450
			400	320-400	6-10	NZMC3-A400-SVE 168451
			500	400-500	6-10	NZMC3-A500-SVE 168452
	4-pole	36	320	250-320	6-10	NZMC3-4-A320-SVE 168464
			320/200	250-320	6-10	NZMC3-4-A320/200-SVE 168465
			400	320-400	6-10	NZMC3-4-A400-SVE 168466
			400/250	320-400	6-10	NZMC3-4-A400/250-SVE 168467
			500	400-500	6-10	NZMC3-4-A500-SVE 168468
			500/320	400-500	6-10	NZMC3-4-A500/320-SVE 168469
Normal switching capacity						
	3-pole	50	320	250-320	6-10	NZMN3-A320-SVE 168486
			400	320-400	6-10	NZMN3-A400-SVE 168487
			500	400-500	6-10	NZMN3-A500-SVE 168488
	4-pole	50	320	250-320	6-10	NZMN3-4-A320-SVE 168508
			320/200	250-320	6-10	NZMN3-4-A320/200-SVE 168509
			400	320-400	6-10	NZMN3-4-A400-SVE 168510
			400/250	320-400	6-10	NZMN3-4-A400/250-SVE 168511
			500	400-500	6-10	NZMN3-4-A500-SVE 168512
			500/320	400-500	6-10	NZMN3-4-A500/320-SVE 168513
High switching capacity						
	3-pole	150	320	250-320	6-10	NZMH3-A320-SVE 168913
			400	320-400	6-10	NZMH3-A400-SVE 168914
			500	400-500	6-10	NZMH3-A500-SVE 168915
	4-pole	150	320	250-320	6-10	NZMH3-4-A320-SVE 168889
			320/200	250-320	6-10	NZMH3-4-A320/200-SVE 168890
			400	320-400	6-10	NZMH3-4-A400-SVE 168891
			400/250	320-400	6-10	NZMH3-4-A400/250-SVE 168892
			500	400-500	6-10	NZMH3-4-A500-SVE 168893
			500/320	400-500	6-10	NZMH3-4-A500/320-SVE 168894