









Description	For use with	Part no. Article no.	Price see price list	Std. pack	Instructions
Power supply at flat cable RA-C1					
Flexible busbar junction 400 V AC/24 V DC Connection socket for power connection cable					
	Insulation piercing terminals, terminal socket with lock mechanism	RA-C1-7X4HF RA-C3/C1-1,5HF	RA-C1-PLF 290188	5 off	-
Protection cover for protecting the 400 V AC/24 V DC flexible busbar junction					
	-	RA-C1-PLF	RA-C1-COV 254693	10 off	-
Plug connector for 400 V AC/24 V DC flexible busbar junction					
	Plug insert with hood	RA-C1-PLF	RA-C1-VP-PLM 231574	5 off	Order cable gland V-M25 separately.
Distributor module for feeding the 400-V-AC/24-V-DC of the ribbon cable with a round cable					
	Termination with piercing screws, 2 x V-M25 and 2 x V-M20 knockout plates, connection module with spring-loaded terminals, connection of round cables up to 4 mm ² .	RA-C1-7X4HF	RA-C1-AM-7 290214	5 off	Order cable gland V-M25 or V-M20 separately.
Power/AS-Interface connection cable for connecting the device with the 400 V AC AS-Interface flexible busbar junction					
	Double cable with outgoer plug (flexible busbar end) and M12 plug and power plug (device end)	RAMO RASP RA-C1-PLF1	RA-C1-PLM/C3-1M5 112624	1 off	Can be used when AS-Interface implemented in flat cable.
400 V AC/AS-Interface flexible busbar junction Connection socket for power/AS-Interface cable					
	Insulation piercing terminals, terminal socket with lock mechanism	RA-C1-7X4HF RA-C1-PLM/C3-1M5	RA-C1-PLF1 116904	1 off	Can be used when AS-Interface implemented in flat cable.
Power/AS-Interface connection cable For connecting the device with 400 V AC/24 V DC/AS-Interface flexible busbar					
	Double cable with connection module (flexible busbar end) and M12 plug as well as power plug (device end), termination with piercing screws, knockouts Length 1.5 m	RAMO RASP RA-C1-7X4HF	RA-C1-AM/C3-1M5 112625	1 off	Can be used when AS-Interface implemented in flat cable.
Distributor module for the 400V AC feeding to the ribbon cable with a round cable					
	With 3 flexible busbar inputs and 2 round cable inputs Connection of round cables 4 mm ²	RA-C1-7X4HF	RA-C1-VM-7 264244	2 off	Order V-M25/V-M20 cable gland and RA-C1-DF bushing separately.
Flexible busbar bushing for bushing for flat cable in distributor module or control cabinet					
	-	RA-C1-VM-7	RA-C1-DF 264243	10 off	-
Distributor module 24 V DC control voltage is taken from the ribbon cable					
	Termination with piercing screws, connection sockets with screw contacts	RA-C1-7X4HF	RA-C1-VP-AM-2 264315	5 off	Order cable gland V-M20 separately
Flexible busbars for fastening the ribbon cable					
	-	RA-C1-7X4HF	RA-C1-FIX 272086	100 off	One set with 100 clips.