



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	M35/16
Product ID:	1SNA115124R0700
EAN:	3472591151244
Catalog Description:	M35/16 Screw Clamp Terminal Blocks - Feed-through - Grey
Long Description:	M35/16 Screw Clamp Terminal Blocks - Feed-through - Grey, 35mm ² RatedCrossSection, 16mm Spacing G32, TH 35-7.5, TH 35-15 Rail

Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » SNA Series

Ordering

Minimum Order Quantity:	20 piece
Customs Tariff Number:	85369010
Color:	Grey

Dimensions

Product Net Height:	49 mm
Product Net Depth:	46.5 mm
Product Net Weight:	50 g
Product Net Width:	16 mm

Technical

Spacing:	16 mm
Connection Type:	Screw clamp
Function:	Feed-through
Number of Levels:	1
Connecting Capacity-Main Circuit:	Screw Clamp / Flexible 1x 1 ... 35 mm ² Screw Clamp / Rigid 1x 1 ... 50 mm ² Screw Clamp / With Insulated Ferrule 1x 35 mm ²
Gauge Type:	B9
Rated Current (I _n):	Main Circuit 125 A
Rated Short-time Withstand Current (I _{cw}):	for 1 s 4200 A
Rated Voltage (U _r):	1000 V
Rated Impulse Withstand Voltage (U _{imp}):	8000 V
Dielectric Test Voltage:	3500 V
Pollution Degree:	3
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Insulation Material:	Polyamide
Mounting on DIN Rail:	G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Wire Stripping Length:	17.0 mm
Recommended Screw Driver:	6.5 ... 7 mm
Tightening Torque:	acc. IEC 60947-1 2.8 N·m Manufacturer 3 N·m
Rated Cross-Section:	35 mm ²

Technical UL/CSA

Connecting Capacity Main Circuit UL/CSA:	Screw Clamp / Rigid 1x 10 ... 0 AWG
Connecting Capacity UL/CSA:	Screw Clamp / Rigid 10 ... 0 AWG Stranded 0 AWG
Flammability According to UL94:	V0
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V

Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C

Certificates and Declarations (Document Number)

CSA Certificate:	1SND161051A0202
cUL Certificate:	1SND161001A0208
Declaration of Conformity - CE:	1SND225001C1009
EAC Certificate:	1SND161009A1100
RoHS Information:	1SND230023F0208

Classifications

E-nummer:	2925516
ETIM 4:	EC000897 - Feed-through terminal block
ETIM 5:	EC000897 - Feed-through terminal block
Object Classification Code:	X

Container Information

Package Level 1 Width:	81 mm
Package Level 1 Length:	200 mm
Package Level 1 Height:	53 mm
Package Level 1 Gross Weight:	1 kg
Package Level 1 EAN:	3472591151244
Package Level 2 Units:	300 piece
Package Level 2 Width:	300 mm
Package Level 2 Length:	500 mm
Package Level 2 Height:	150 mm
Package Level 2 Gross Weight:	15.350 kg
Package Level 3 Units:	14400 piece
Product Packing Type:	Box
Package Level 1 Units:	20 piece



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
M35/16 Screw Clamp Terminal Blocks - Feed-through - Grey	1SNA115124R0700	M35/16	Buy on EAN