



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	M35/26.FF
Product ID:	1SNA115140R2300
EAN:	3472591151404
Catalog Description:	M35/26.FF
Long Description:	M35/26.FF Power Terminal Blocks - Feed-through - Grey, 25mm ² RatedCrossSection, 26mm Spacing G32, TH 35-7.5, TH 35-15 Rail

Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » Solution Series

Ordering

EAN:	3472591151404
Minimum Order Quantity:	10 piece
Customs Tariff Number:	85369010

Dimensions

Product Net Width:	26 mm
Product Net Height:	66 mm
Product Net Depth:	44 mm
Product Net Weight:	64 g

Container Information

Package Level 1 Units:	10 piece
Package Level 1 Width:	120 mm
Package Level 1 Height:	57 mm
Package Level 1 Length:	130 mm
Package Level 1 Gross Weight:	0.64 kg
Package Level 1 EAN:	3472591151404
Package Level 2 Units:	300 piece
Package Level 2 Width:	300 mm
Package Level 2 Height:	300 mm
Package Level 2 Length:	500 mm
Package Level 2 Gross Weight:	19.7 kg
Package Level 3 Units:	7200 piece
Product Packing Type:	Box

Environmental

Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C
RoHS Status:	Following EU Directive 2011/65/EC

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Main Circuit 600 V
Connecting Capacity Main Circuit UL/CSA:	Stud / Rigid 1x 10 ... 2 AWG
Connecting Capacity UL/CSA:	Stranded 2 AWG

Additional Information

Ambient Temperature:	-5 ... +40 °C
Color:	Grey
Connecting Capacity-Main Circuit:	Stud / Flexible 1x 2.5 ... 25 mm ² Stud / Rigid 1x 2.5 ... 50 mm ²
Connection Type:	Stud
Function:	Feed-through
IIT Publishing Status:	Level 0 - Information enabled
Insulation Material:	Polyamide
Mounting on DIN Rail:	G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Number of Levels:	1
Pollution Degree:	3

Product Main Type:	M35/26.FF
Product Name:	Terminal block
Rated Cross-Section:	25 mm ²
Rated Current (I_n):	Main Circuit 101 A
Rated Short-time Withstand Current (I_{cw}):	for 1 s 8000 A
Rated Voltage (U_r):	1000 V
RoHS Date:	20140212
Spacing:	26 mm
Sub-Function 3:	2 connections
Tightening Torque:	Cable Lug 9 N·m

Certificates and Declarations (Document Number)

cUL Certificate:	1SND165000A0203
Data Sheet, Technical Information:	1SNC160020C0201
Declaration of Conformity - CE:	1SND225008C1006
EAC Certificate:	1SND161009A1100
RoHS Information:	1SND230022F0204

Classifications

ETIM 4:	EC000897 - Feed-through terminal block
ETIM 5:	EC000897 - Feed-through terminal block
Object Classification Code:	X



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
M35/26.FF	1SNA115140R2300	M35/26.FF	Buy on EAN