



**Automatización Eléctrica**  
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

### General Information

Extended Product Type:	M4/6.G
Product ID:	1SNA115190R1600
EAN:	3472591151909
Catalog Description:	M4/6.G Specific Terminal Blocks Feed-through Grey
Long Description:	M4/6.G Specific Terminal Blocks - Feed-through - Grey, 4mm <sup>2</sup> Rated Cross Section, 6mm Spacing G32, TH 35-7.5, TH 35-15 Rail

### Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » Solution Series

### Ordering

Minimum Order Quantity:	50 piece
Customs Tariff Number:	85369010
Color:	Grey

### Dimensions

Product Net Height:	44.5 mm
Product Net Depth:	40.5 mm
Product Net Weight:	8 g
Product Net Width:	6 mm

### Technical

Spacing:	6 mm
Connection Type:	Quick-connect - Screw clamp
Function:	Feed-through
Number of Levels:	1
Connecting Capacity-Main Circuit:	Screw Clamp / Flexible 1x 0.5 ... 4 mm <sup>2</sup> Screw Clamp / Rigid 1x 0.5 ... 4 mm <sup>2</sup>
Rated Current (I <sub>n</sub> ):	Main Circuit 25 A
Rated Short-time Withstand Current (I <sub>cw</sub> ):	for 1 s 480 A
Rated Voltage (U <sub>r</sub> ):	750 V
Pollution Degree:	2
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Insulation Material:	Polyamide
Mounting on DIN Rail:	G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Wire Stripping Length:	9.5 mm
Recommended Screw Driver:	4 mm
Tightening Torque:	acc. IEC 60947-1 0.4 N·m Manufacturer 0.6 N·m
Rated Cross-Section:	4 mm <sup>2</sup>

### Technical UL/CSA

Connecting Capacity Main Circuit UL/CSA:	Screw Clamp / Rigid 1x 22 ... 10 AWG
Flammability According to UL94:	V2
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V

### Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007-01-01
Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C

### Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	1SND225003C1007
EAC Certificate:	1SND161009A1100
RoHS Information:	1SND230021F0201

## Classifications

**ETIM 4:** EC000897 - Feed-through terminal block

**ETIM 5:** EC000897 - Feed-through terminal block

**Object Classification Code:** X

## Container Information

**Package Level 1 Width:** 61 mm

**Package Level 1 Length:** 220 mm

**Package Level 1 Height:** 47 mm

**Package Level 1 Gross Weight:** 0.4 kg


**Package Level 1 EAN:** 3472591151909

**Package Level 2 Units:** 1000 piece

**Package Level 3 Units:** 48000 piece

**Product Packing Type:** Box

**Package Level 1 Units:** 50 piece



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

<b>Product</b>	<b>Code</b>	<b>Reference</b>	<b>Product link</b>
M4/6.G Specific Terminal Blocks Feed-through Grey	1SNA115190R1600	M4/6.G	<a href="#">Buy on EAN</a>