



**Automatización Eléctrica**  
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

### General Information

Extended Product Type:	M2.5/6.2G.2G
Product ID:	1SNA115191R0300
EAN:	3472591151916
Catalog Description:	M2.5/6.2G.2G Specific Terminal Blocks Feed-through Grey
Long Description:	M2.5/6.2G.2G Specific Terminal Blocks - Feed-through - Grey, 2.5mm <sup>2</sup> RatedCrossSection, 6mm Spacing G32, TH 35-7.5, TH 35-15 Rail

### Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » Solution Series

### Ordering

Minimum Order Quantity:	50 piece
Customs Tariff Number:	85369010
EAN:	3472591151916

### Dimensions

Product Net Height:	44.5 mm
Product Net Depth:	40.5 mm
Product Net Weight:	8 g
Product Net Width:	6 mm

### Container Information

Package Level 1 Width:	61 mm
Package Level 1 Length:	220 mm
Package Level 1 Height:	47 mm
Package Level 1 Gross Weight:	0.4 kg
Package Level 1 EAN:	3472591151916
Package Level 2 Units:	1000 piece
Package Level 3 Units:	48000 piece
Product Packing Type:	Box
Package Level 1 Units:	50 piece

### Technical

Spacing:	6 mm
Connection Type:	Quick-connect
Function:	Feed-through
Number of Levels:	1
Rated Current (I <sub>n</sub> ):	Main Circuit 25 A
Rated Short-time Withstand Current (I <sub>cw</sub> ):	for 1 s 300 A
Rated Voltage (U <sub>r</sub> ):	630 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> ):	6000 V
Dielectric Test Voltage:	3500 V
Pollution Degree:	2
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Insulation Material:	Polyamide
Mounting on DIN Rail:	G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Rated Cross-Section:	2.5 mm <sup>2</sup>

### Technical UL/CSA

Flammability According to UL94:	V2
---------------------------------	----

### Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007 Q1
Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C

### Certificates and Declarations (Document Number)

**Declaration of Conformity - CE:** 1SND225003C1007

**EAC Certificate:** 1SND161009A1100

**RoHS Information:** 1SND230021F0201

---

### Classifications

---

**ETIM 4:** EC000897 - Feed-through terminal block

**ETIM 5:** EC000897 - Feed-through terminal block

**Object Classification Code:** X

---



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

<b>Product</b>	<b>Code</b>	<b>Reference</b>	<b>Product link</b>
M2.5/6.2G.2G Specific Terminal Blocks Feed-through Grey	1SNA115191R0300	M2.5/6.2G.2G	<a href="#">Buy on EAN</a>