



**Automatización Eléctrica**  
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

## General Information

Extended Product Type:	M6/8.S
Product ID:	1SNA115234R1500
EAN:	3472591152340
Catalog Description:	M6/8.S Screw Clamp Terminal Blocks - Disconnect with Plug - Grey
Long Description:	M6/8.S Screw Clamp Terminal Blocks - Disconnect - Grey, 6mm <sup>2</sup> RatedCrossSection, 8mm Spacing G32, TH 35-7.5, TH 35-15 Rail

## Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » Solution Series

## Ordering

Minimum Order Quantity:	50 piece
Customs Tariff Number:	85369010
Color:	Grey

## Dimensions

Product Net Height:	44.5 mm
Product Net Depth:	40.5 mm
Product Net Weight:	16 g
Product Net Width:	8 mm

## Technical

Spacing:	8 mm
Connection Type:	Screw clamp
Function:	Disconnect
Number of Levels:	1
Connecting Capacity-Main Circuit:	Screw Clamp / Flexible 1x 0.5 ... 6 mm <sup>2</sup> Screw Clamp / Rigid 1x 0.5 ... 10 mm <sup>2</sup>
Gauge Type:	A5
Rated Current (I <sub>n</sub> ):	Main Circuit 16 A
Rated Short-time Withstand Current (I <sub>cw</sub> ):	for 1 s 180 A
Rated Voltage (U <sub>r</sub> ):	160 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> ):	2500 V
Pollution Degree:	3
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Insulation Material:	Polyamide
Mounting on DIN Rail:	G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Wire Stripping Length:	12.0 mm
Recommended Screw Driver:	4.5 mm
Tightening Torque:	acc. IEC 60947-1 0.8 N·m Manufacturer 1 N·m
Rated Cross-Section:	6 mm <sup>2</sup>

## Technical UL/CSA

Connecting Capacity Main Circuit UL/CSA:	Screw Clamp / Rigid 1x 22 ... 8 AWG
Connecting Capacity UL/CSA:	Stranded 8 AWG
Flammability According to UL94:	V0
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V

## Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C

## Certificates and Declarations (Document Number)

cUL Certificate:	1SND161001A0208
------------------	-----------------

<b>Declaration of Conformity - CE:</b>	1SND225002C1007
<b>EAC Certificate:</b>	1SND161009A1100
<b>RoHS Information:</b>	1SND230023F0208

### Classifications

<b>E-nummer:</b>	2925577
<b>ETIM 4:</b>	EC000902 - (Knife) disconnect terminal block
<b>ETIM 5:</b>	EC000902 - (Knife) disconnect terminal block
<b>Object Classification Code:</b>	X

### Container Information

<b>Package Level 1 Width:</b>	101 mm
<b>Package Level 1 Length:</b>	220 mm
<b>Package Level 1 Height:</b>	47 mm
<b>Package Level 1 Gross Weight:</b>	0.8 kg
<b>Package Level 1 EAN:</b>	3472591152340
<b>Package Level 2 Units:</b>	500 piece
<b>Package Level 2 Width:</b>	300 mm
<b>Package Level 2 Length:</b>	500 mm
<b>Package Level 2 Height:</b>	150 mm
<b>Package Level 2 Gross Weight:</b>	8.35 kg
<b>Package Level 3 Units:</b>	24000 piece
<b>Product Packing Type:</b>	Box
<b>Package Level 1 Units:</b>	50 piece



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

<b>Product</b>	<b>Code</b>	<b>Reference</b>	<b>Product link</b>
M6/8.S Screw Clamp Terminal Blocks - Disconnect with Plug - Grey	1SNA115234R1500	M6/8.S	<a href="#">Buy on EAN</a>