



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	M6/8.ST3
Product ID:	1SNA115239R2200
EAN:	3472591152395
Catalog Description:	M6/8.ST3 Screw Clamp Terminal Blocks - Test disconnect with insulated rod sliding link - Grey
Long Description:	M6/8.ST3 Screw Clamp Terminal Blocks - Disconnect - Grey,6mm ² RatedCrossSection, 8mm Spacing G32, TH 35-7.5, TH 35-15 Rail

Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » SNA Series

Ordering

Minimum Order Quantity:	25 piece
Customs Tariff Number:	85365011
EAN:	3472591152395

Dimensions

Product Net Height:	77 mm
Product Net Depth:	41 mm
Product Net Weight:	30 g
Product Net Width:	8 mm

Container Information

Package Level 1 Width:	82 mm
Package Level 1 Length:	265 mm
Package Level 1 Height:	65 mm
Package Level 1 Gross Weight:	0.75 kg
Package Level 1 EAN:	3472591152395
Package Level 2 Units:	250 piece
Package Level 2 Width:	300 mm
Package Level 2 Length:	500 mm
Package Level 2 Height:	150 mm
Package Level 2 Gross Weight:	7.850 kg
Package Level 3 Units:	12000 piece
Product Packing Type:	Box
Package Level 1 Units:	25 piece

Technical

Spacing:	8 mm
Connection Type:	Screw clamp
Function:	Disconnect
Number of Levels:	1
Connecting Capacity-Main Circuit:	Screw Clamp / Flexible 1x 0.5 ... 6 mm ² Screw Clamp / Rigid 1x 0.5 ... 10 mm ²
Gauge Type:	A5
Rated Current (I _n):	Main Circuit 40 A
Rated Short-time Withstand Current (I _{cw}):	for 1 s 720 A
Rated Voltage (U _r):	630 V
Pollution Degree:	3
Insulation Material:	Polyamide
Mounting on DIN Rail:	G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Wire Stripping Length:	13.0 mm
Recommended Screw Driver:	5 mm
Tightening Torque:	acc. IEC 60947-1 0.8 N·m Manufacturer 1 N·m
Rated Cross-Section:	6 mm ²

Technical UL/CSA

**Connecting Capacity Main Circuit
UL/CSA:** Screw Clamp / Rigid 1x 18 ... 8 AWG

Connecting Capacity UL/CSA: Stranded 8 AWG

Flammability According to UL94: V0

**Maximum Operating Voltage
UL/CSA:** Main Circuit 150 V

Environmental

RoHS Status: Following EU Directive 2002/95/EC August 18, 2005 and amendment

Ambient Air Temperature: Operation -55 ... +110 °C
Storage -55 ... +110 °C

Certificates and Declarations (Document Number)

CSA Certificate: 1SND161039A0201

cUL Certificate: 1SND161001A0208

Declaration of Conformity - CE: 1SND225002C1007

EAC Certificate: 1SND161009A1100

RoHS Information: 1SND230023F0208

Classifications

ETIM 4: EC000902 - (Knife) disconnect terminal block

ETIM 5: EC000902 - (Knife) disconnect terminal block

Object Classification Code: X



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
M6/8.ST3 Screw Clamp Terminal Blocks - Test disconnect with insulated rod sliding link - Grey	1SNA115239R2200	M6/8.ST3	Buy on EAN